




INSTAFLEX Riduzione elettrosaldabile polibutene

- Materiale: Polibutene (grigio)
- * finché durano le previste



d1	d2	code	NPK	SP	weight	l	h	z
(mm)	(mm)				(kg)	(mm)	(mm)	(mm)
20	16	761 069 277	444 312	1	0.023	40	83	45
25	16	761 069 278	444 313	1	0.026	42	83	46
25	20	761 069 279		1	0.026	42	86	47
32	16	761 069 457	444 314	1	0.033	42	86	48
32	20	761 069 280		1	0.030	42	84	45
32	25	761 069 281		1	0.038	42	89	47
40	20	761 069 458		1	0.055	47	102	62
40	25	761 069 459		1	0.060	47	104	62
40	32	761 069 282	444 315	1	0.060	47	95	53
50	20	761 069 460		1	0.070	49	102	62
50	25	761 069 461		1	0.075	49	104	62
50	32	761 069 462		1	0.075	49	95	53
50	40	761 069 283	444 316	1	0.091	49	103	56
*	63	761 069 463		1	0.096	51	102	62
63	25	761 069 464		1	0.109	51	104	62
63	32	761 069 284		1	0.101	51	95	53
63	40	761 069 465	444 317	1	0.121	51	103	56
63	50	761 069 285		1	0.141	51	106	57
75	63	761 069 286	444 318	1	0.232	67	129	78
90	63	761 069 287	444 321	1	0.289	74	128	77
90	75	761 069 288		1	0.354	74	143	76
110	63	761 069 289	444 322	1	0.414	80	135	84
110	75	761 069 290		1	0.464	80	150	83
110	90	761 069 291		1	0.576	80	165	92

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>