



ELGEF Plus Electrofusion coupler PE100 d355-800mm / SDR11

- 10 bar Gas / 16 bar Water
 - 4mm pin connectors
 - Limited path fusion indicators
 - With active reinforcement
 - Material: monofilament
 - Ø355 – 500 have two connected (monofilar) welding zones (Both pipe ends can be welded simultaneously)
 - Ø560 – 800 have two separate (bifilar) welding zones (Both pipe ends welded separately)
- ¹⁾ FM 1613 approved – 15 bar

	d	SDR	PN	DN	Code	Weight	d1	L	SDR pipe
	(mm)		(bar)	(mm)		(kg)	(mm)	(mm)	
1	355	11	16	350	753 911 704	13.098	438	291	9-17
1	400	11	16	400	753 911 705	18.320	493	295	9-17
1	450	11	16	450	753 911 706	24.700	554	327	9-17
1	500	11	16	500	753 911 707	33.700	616	358	9-17
	560	11	16	600	753 911 708	46.200	689	396	9-17
	630	11	16	600	753 911 709	65.300	775	440	9-17
	710	11	16	700	753 911 710	97.400	874	463	9-17
	800	11	16	800	753 911 711	114.500	982	484	9-17

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>