



Ball valve

- Temperature: max. -20°C / +120°C (water, compressed air, oil, petrol)
 - Material: brass nickel-plated / 58 hard chrome-plated, PTFE
- *as long as stock last

DN (mm)	GN (inch)	Size (inch)	JRG Code	GF Code	SP	Weight (kg)
8	¼	¼	6020.080	355 635 515	1	0.15
10	¾	¾	6020.160	355 635 516	1	0.12
15	½	½	6020.240	355 635 517	1	0.23
20	¾	¾	6020.320	355 635 518	1	0.37
25	1	1	6020.400	355 635 519	1	0.52
32	1 ¼	1 ¼	6020.480	355 635 520	1	0.87
40	1 ½	1 ½	6020.560	355 635 521	1	1.24
50	2	2	6020.640	355 635 522	1	2.00
65	2 ½	2 ½	6020.720	355 635 523	1	3.75
*	80	3	6020.800	355 635 524	1	5.98

DN (mm)	d1 (inch)	Rp (mm)	h (mm)	l (mm)	l1 (mm)	s (mm)	z (mm)	kv-value (Δp=1 bar) (L/min)	PN (bar)
8	¼	46.5	51.5	95	20	29.5	5.4	64	
10	¾	46.5	51.5	95	20	28.7	6.0	64	
15	½	50.0	62.0	95	25	32.0	16.3	64	
20	¾	62.0	69.0	110	31	36.4	29.5	50	
25	1	66.0	83.0	110	38	44.8	43.0	50	
32	1 ¼	79.0	96.0	160	48	53.2	89.0	50	
40	1 ½	85.5	108.0	160	54	65.2	230.0	40	
50	2	103.0	127.5	170	67	76.1	265.0	40	
65	2 ½	129.0	152.0	205	90	91.6	540.0	25	
*	80	3	140.0	177.0	205	105	110.4	873.0	25

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>