



Wafer-style intermediate installation butterfly valve type 240 PVC-C
FC (Fail safe to close)
Flange standard metric/ANSI/BS/JIS

Model:

- Overall length according to EN 558, ISO 5752
- Connecting dimension: ISO 7005 PN 10, EN 1092 PN 10, DIN 2501 PN 10, ANSI/ASME B 16.5 Class 150, BS 1560: 1989, BS 4504, JIS B 2220
- Control pressure supply through integrated NAMUR interface according VDI/VDE 3845 with 4.2 bar (60.9 psi)
- Control time 90°<) 1-2s
- For easy installation and removal
- Full plastic solution (actuator housing made of PP-GF)
- Visual position indicator

Option:

- Positioner RPC, RPC D, RPC PID
- Optional accessory: Valve-Integrated position feedback with limit switches (limit switches have to be ordered separately)
- Individual configuration of the valve

Note:

For some material combination (e.g. DN300 valves with PE/PP pipes) special flange adapters are needed. Please check the "Perfect flange connection tool" on www.gfps.com

d (mm)	Size (inch)	DN (mm)	EPDM Code	SP	Weight (kg)	FKM Code	SP	Weight (kg)
63	2	50	199 240 992	1	3.218	199 240 982	1	3.218
75	2 ½	65	199 240 993	1	3.341	199 240 983	1	3.352
90	3	80	199 240 994	1	3.524	199 240 984	1	3.531
110	4	100	199 240 995	1	5.271	199 240 985	1	5.371
140	5	125	199 240 996	1	7.169	199 240 986	1	5.943

d (mm)	Hmax (mm)	Lmax (mm)	Wmax (mm)	U (mm)	V (mm)	H4 (mm)	V1 (mm)	Lg (mm)	D2 (mm)	Q1 (mm)	Q2 (mm)	Y (mm)	E (mm)	Y1 (mm)
63	338.1	245.5	121.2	90	133.3	23	78.8	45	104	40		111	119.5	15
75	351.0	245.5	132.5	90	139.9	23	85.1	46	115	54	35	111	119.5	15
90	382.8	343.0	136.8	90	145.6	23	91.2	49	131	67	50	131	141.5	15
110	403.1	343.0	161.0	90	166.4	23	105.7	56	161	88	74	131	141.5	
140	429.8	343.0	187.0	90	180.0	23	118.8	64	187	113	97	131	141.5	

d (mm)	M2 (mm)
63	122.75
75	122.75
90	171.50
110	171.50
140	171.50

Data sheet



valid from: 2/8/25

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>