



JRG LegioStop distributor battery complete gunmetal - new

- Temperature: max. 30°C
- Material: gunmetal, stainless steel, EPDM, plastic
- Factory setting: PRV 400 kPa (4 bar) adjustment range 200 - 600 kPa (2 - 6 bar), safety valve 600 kPa (6 bar)
- Connection: male thread
- Consisting of: JRGUSIT NG battery valve 5151, JRGURED 1303, JRGUSIT Combi distribution fitting 5191
- Thread type d1 = G
- Thread type d2 = G
- Thread type d3 = G
- Thread type d4 = Rp
- Thread type d5 = Rp
- Thread type d6 = Rp
- Thread type d7 = G
- Thread type d8 = G
- Thread type d9 = G

DN (mm)	Size (inch)	JRG Code	GF Code	SP	Weight (kg)
25	1	1511.400	355 623 519	1	5.705
32	1 ¼	1511.480	355 623 529	1	5.863

d1 (inch)	d2 (inch)	d3 (inch)	d4 (inch)	d5 (inch)	d6 (inch)	d7 (inch)	d8 (inch)	d9 (inch)	d10	h1 (mm)	h2 (mm)	h3 (mm)	h4 (mm)	l (mm)
1 ¼	1	1 ¼	¾	¾	¾	¾	1	½	TR 30 x 1.5	55	77	55	90	586
1 ½	1	1 ¼	¾	¾	¾	¾	1	½	TR 30 x 1.5	56	77	67	109	618

l1 (mm)	l2 (mm)	l3 (mm)	l4 (mm)	l5 (mm)	l6 (mm)	PN (bar)
37	133	93	145	130	48	16
42	149	104	145	130	48	16

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>