



PROGEF Standard Ball valve type 180
100-230V
With manual emergency override
With fusion sockets PP-H ISO

Model:

- IP68 Rating
- Factory set control range 90°<
- Heating element, position feedback (Open/Close/ Middle)
- Integrated stainless steel mounting inserts

Option:

- Other valve and actuator configurations available
- Optional accessories: Monitoring board, Positioner, Profibus DP board, Modbus TCP EA 25-250 Ethernet Interface Card

d (mm)	DN (mm)	Size (inch)	PN (bar)	kv-value (Δp=1 bar) (l/min)	EPDM Code	Weight (kg)	FKM Code	Weight (kg)
16	10	3/8	10	70	199 180 002	2.100	199 180 012	2.100
20	15	1/2	10	185	199 180 003	2.439	199 180 013	2.100
25	20	3/4	10	350	199 180 004	2.200	199 180 014	2.200
32	25	1	10	700	199 180 005	2.577	199 180 015	2.589
40	32	1 1/4	10	1000	199 180 006	2.763	199 180 016	2.600
50	40	1 1/2	10	1600	199 180 007	3.000	199 180 017	3.000
63	50	2	10	3100	199 180 008	3.800	199 180 018	3.482
75	65	2 1/2	10	5000	199 180 009	6.200	199 180 019	6.200
90	80	3	10	7000	199 180 010	7.200	199 180 020	7.200
110	100	4	10	11000	199 180 011	11.200	199 180 021	11.200

d (mm)	DE1 (mm)	E (mm)	G (mm)	H (mm)	H1 (mm)	H4 (mm)	Lz (mm)	M (mm)	M1 (mm)	M2 (mm)	L (mm)	L1 (mm)	z (mm)	Actuator	B3 (mm)
16	50	122	M6	227	27	12	28	180	97	83	93	33	67	EA25	25
20	50	122	M6	227	27	12	28	180	97	83	95	33	66	EA25	25
25	58	122	M6	231	30	12	33	180	97	83	109	33	77	EA25	25
32	68	122	M6	237	36	12	36	180	97	83	119	33	83	EA25	25
40	84	122	M8	243	44	15	43	180	97	83	135	33	99	EA25	45
50	97	122	M8	249	51	15	45	180	97	83	147	33	105	EA25	45
63	124	122	M8	264	64	15	51	180	97	83	168	33	117	EA25	45
75	166	122	M8	313	85	15	68	180	98	82	233	33	167	EA45	70
90	200	122	M8	325	105	15	71	180	98	82	254	33	180	EA45	70
110	238	122	M12	363	123	22	82	180	98	82	301	33	215	EA120	120

Data sheet



valid from: 2/8/25

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>