



Fixed flange PVC-U Jointing face flat metric

Model:

- **Bolt circle PN 10**
- Solvent cement socket metric
- Connecting dimension: ISO 7005 PN 10, EN 1092 PN 10, DIN 2501 PN 10, BS 4504 PN 10
- * Combined Flange, connecting dimensions EN1092 PN 10 and ANSI B 16.5 Class 150

d	DN	Size	PN	Code	SP	Weight
(mm)	(mm)	(inch)	(bar)			(kg)
20	15	½	16	721 730 206	0	0.098
25	20	¾	16	721 730 207	0	0.130
32	25	1	16	721 730 208	0	0.183
40	32	1 ¼	16	721 730 209	0	0.305
50	40	1 ½	16	721 730 210	0	0.365
63	50	2	16	721 730 211	0	0.510
*	75	2 ½	10	721 730 212	10	0.520
*	90	3	10	721 730 213	16	0.720
*	110	4	10	721 730 214	12	0.920
*	140	5	10	721 730 216	1	1.380
*	160	6	10	721 730 217	1	2.039

	d	D	D1	D2	D3	z	H	H1	AL	SC
	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)		
	20	95	65	27	14	3	12	19	4	M12
	25	105	75	33	14	3	13	22	4	M12
	32	115	85	41	14	3	14	25	4	M12
	40	140	100	51	18	3	17	29	4	M16
	50	150	110	62	18	3	17	34	4	M16
	63	165	125	77	18	3	20	41	4	M16
*	75	185	142	91	22	3	21	47	4	M20
*	90	200	156	108	22	5	22	56	8	M20
*	110	220	186	131	24	5	24	66	8	M20
*	140	250	215	165	23	5	28	91	8	M20
*	160	285	240	188	23	5	30	91	8	M20

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>