



CONTAIN-IT Plus Ball valve type 546 Pro PP-H/PE100 Connections for butt fusion

Model:

- Manual operated
- Manual override with ratchet setting
- Pneumatic or electric actuator available separately
- Protective housing PVC-U PN6 / sealing according to inner pipe
- For easy installation and removal

d (mm)	D (mm)	PN (bar)	PN (Outer Pipe) (bar)	SDR	EPDM Code	Weight (kg)	FKM Code	Weight (kg)
20	50	10	6	11	727 239 206	4.500	727 239 226	4.500
25	50	10	6	11	727 239 207	7.000	727 239 227	7.000
32	63	10	6	11	727 239 208	7.300	727 239 228	7.300
40	75	10	6	11	727 239 209	9.800	727 239 229	9.800
50	90	10	6	11	727 239 210	11.800	727 239 230	11.800
63	110	10	6	11	727 239 211	13.200	727 239 231	13.200

d (mm)	ZA 1 (mm)	ZA 2 (mm)	Zi 1 (mm)	Zi 2 (mm)	H (mm)	H1 (mm)	H2 (mm)
20	255	330	275	350	222	182	85
25	255	330	275	350	222	182	85
32	275	355	295	375	234	194	105
40	325	410	345	430	244	210	123
50	340	425	360	445	244	210	123
63	350	480	370	500	244	210	123

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>