




## 90° Elbow with threaded male off take

- installation without disassembling
- suitable for PE and PEX pipes
- water PN16
- material: PP
- gasket: EPDM quality for drinkable water
- male thread: ISO 7 (conical)
- colour: blue-black



| d    | R      | PN    | Code        | SP | GP  | Weight | D    | L    | I1   | I2   | I3   | H    |
|------|--------|-------|-------------|----|-----|--------|------|------|------|------|------|------|
| (mm) | (inch) | (bar) |             |    |     | (kg)   | (mm) | (mm) | (mm) | (mm) | (mm) | (mm) |
| 16   | ½      | 16    | 158 400 357 | 10 | 60  | 0.046  | 46   | 91   | 46   | 19   | 14   | 41   |
| 20   | ½      | 16    | 158 400 047 | 10 | 200 | 0.044  | 45   | 67   | 54   | 19   | 14   | 41   |
| 20   | ¾      | 16    | 158 400 048 | 10 |     | 0.046  | 45   | 67   | 54   | 19   | 15   | 42   |
| 25   | ½      | 16    | 158 400 049 | 10 | 150 | 0.061  | 53   | 75   | 59   | 21   | 14   | 44   |
| 25   | ¾      | 16    | 158 400 050 | 10 |     | 0.067  | 53   | 75   | 59   | 21   | 15   | 46   |
| 25   | 1      | 16    | 158 400 051 | 10 |     | 0.070  | 53   | 75   | 59   | 21   | 17   | 48   |
| 32   | ½      | 16    | 158 400 052 | 10 | 120 | 0.096  | 64   | 87   | 66   | 23   | 14   | 49   |
| 32   | ¾      | 16    | 158 400 053 | 10 | 110 | 0.100  | 64   | 87   | 66   | 23   | 15   | 51   |
| 32   | 1      | 16    | 158 400 054 | 10 |     | 0.109  | 64   | 87   | 66   | 23   | 17   | 53   |
| 40   | 1      | 16    | 158 400 055 | 70 |     | 0.160  | 75   | 102  | 76   | 26   | 17   | 60   |
| 40   | 1 ¼    | 16    | 158 400 056 | 70 |     | 0.175  | 75   | 102  | 75   | 26   | 20   | 62   |
| 40   | 1 ½    | 16    | 158 400 057 | 70 |     | 0.176  | 75   | 102  | 75   | 26   | 20   | 62   |
| 50   | 1 ¼    | 16    | 158 400 058 | 1  | 45  | 0.305  | 97   | 119  | 88   | 30   | 20   | 70   |
| 50   | 1 ½    | 16    | 158 400 059 | 26 |     | 0.316  | 97   | 117  | 88   | 30   | 20   | 70   |
| 63   | 1 ¼    | 16    | 158 400 060 | 1  | 25  | 0.527  | 114  | 144  | 104  | 35   | 20   | 81   |
| 63   | 1 ½    | 16    | 158 400 061 | 25 |     | 0.538  | 114  | 144  | 104  | 35   | 20   | 81   |
| 63   | 2      | 16    | 158 400 062 | 20 |     | 0.562  | 114  | 144  | 104  | 35   | 24   | 85   |
| 63   | 2 ½    | 16    | 158 400 063 | 1  | 15  | 0.587  | 114  | 144  | 104  | 35   | 28   | 89   |
| 75   | 2 ½    | 16    | 158 400 064 | 1  | 12  | 0.950  | 135  | 180  | 133  | 41   | 28   | 101  |
| 75   | 3      | 16    | 158 400 065 | 1  | 10  | 0.959  | 135  | 180  | 133  | 41   | 30   | 104  |
| 90   | 3      | 16    | 158 400 066 | 6  |     | 1.512  | 161  | 207  | 150  | 44   | 30   | 116  |
| 90   | 4      | 16    | 158 400 067 | 1  | 7   | 1.598  | 161  | 207  | 150  | 44   | 36   | 122  |
| 110  | 3      | 16    | 158 400 068 | 1  | 4   | 2.204  | 185  | 242  | 175  | 53   | 30   | 131  |
| 110  | 4      | 16    | 158 400 069 | 1  | 2   | 2.294  | 185  | 242  | 175  | 53   | 36   | 138  |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>