




Backing flanges PN 16 IPP

Material: Casting, GFK coated
Suitable for flange adaptor
Tighten the screws with torque as indicated
Commercially available screws, nuts, washers
* on request



	d (mm)	Code	SP	Weight (kg)
*	20	761 065 270	2	0.378
*	25	761 065 271	2	0.463
	32	761 065 272	2	0.412
	40	761 065 273	2	0.551
	50	761 065 274	2	0.747
	63	761 065 275	2	0.842
	75	761 065 276	2	1.131
	90	761 065 277	2	1.092
	110	761 065 278	2	1.465

	d (mm)	D (mm)	D1 (mm)	D2 (mm)	D3 (mm)	H (mm)	Tightening torque (mm)	○	SC
*	20	106	65	28	14	18	10	4	M 12x 70
*	25	118	75	34	14	18	15	4	M 12x 75
	32	122	85	42	14	17	15	4	M 12x 75
	40	142	100	51	18	17	20	4	M 16x 80
	50	156	110	62	18	19	25	4	M 16x 85
	63	171	125	78	18	20	35	4	M 16x 85
	75	191	145	92	18	21	40	4	M 16x 90
	90	206	160	110	18	21	40	8	M 16x 90
	110	226	180	133	18	22	50	8	M 16x 95

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>