



**PVC-C Vented Ball valve type 546 Pro V 24V**  
**With manual emergency override**  
**With solvent cement sockets PVC-C ASTM**

**Model:**

- IP68 Rating
- Factory set control range 90°<
- Heating element, position feedback (Open/Close/ Middle)
- Integrated stainless steel mounting inserts
- 3 mm drilled hole inside the ball
- Benefits: Safely releases trapped gas or liquid; Reduces risk of rupture, leakage, and explosion; Protects valve seals and components from pressure-related wear
- Range of use: The vented ball valve is designed for applications such as: chlorinated water, water where bleach (**sodium hypochlorite solutions**) is present, and other applications where liquids requiring out-gassing exist.
- General functions: The special vent on side of the ball allows for pressure to be released back into the closed system. (Upstream) This helps prevent potentially dangerous pressure from building up inside the valve.

**Option:**

- Other valve and actuator configurations available
- Optional accessories: Monitoring board, Positioner, Profibus DP board, Modbus TCP EA 25-250 Ethernet Interface Card

d (mm)	DN (mm)	Size (inch)	PN (bar)	kv-value ( $\Delta p=1$ bar) (l/min)	EPDM Code	Weight (kg)	FKM Code	Weight (kg)
16	10	3/8	10	70	199182422V	2.100	199182432V	2.100
20	15	1/2	10	185	199182423V	2.100	199182433V	2.100
25	20	3/4	10	350	199182424V	2.200	199182434V	2.200
32	25	1	10	700	199182425V	2.300	199182435V	2.300
40	32	1 1/4	10	1000	199182426V	2.600	199182436V	2.600
50	40	1 1/2	10	1600	199182427V	3.000	199182437V	3.000
63	50	2	10	3100	199182428V	3.800	199182438V	3.800
75	65	2 1/2	10	5000	199182429V	7.800	199182439V	7.800
90	80	3	10	7000	199182430V	9.360	199182440V	8.360
110	100	4	10	11000	199182431V	15.000	199182441V	15.000

d (mm)	Actuator	B3 (mm)	DE1 (mm)	E (mm)	G (mm)	H (mm)	H1 (mm)	H4 (mm)	L (mm)	L1 (mm)	Lz (mm)	M (mm)	M1 (mm)	M2 (mm)	z (mm)
16	EA25	25	50	122	M6	227	27	12	92	33	28	180	97	83	64
20	EA25	25	50	122	M6	227	27	12	95	33	28	180	97	83	64
25	EA25	25	58	122	M6	231	30	12	110	33	33	180	97	83	72
32	EA25	25	68	122	M6	237	36	12	123	33	36	180	97	83	79
40	EA25	45	84	122	M8	243	44	15	146	33	43	180	97	83	94
50	EA25	45	97	122	M8	249	51	15	157	33	45	180	97	83	95
63	EA25	45	124	122	M8	264	64	15	183	33	51	180	97	83	107
75	EA45	70	166	122	M8	313	85	15	233	33	68	180	98	82	144
90	EA45	70	200	122	M8	325	105	15	254	33	71	180	98	82	151
110	EA120	120	238	122	M12	363	123	22	301	33	82	180	98	82	174

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: http://www.gfps.com