



Ball valve type 375 PVC-C

With solvent cement sockets Inch ASTM/Inclusive 2 threaded valve ends NPT up to 2" -DN50

Model:

- True double union safe block ball valve
- Ball seat PTFE
- Handle includes integrated tool for ball seat adjustment
- Very compact dimensions
- z-dimension, valve end and union nut are not compatible with type 546
- Combo valve ends reduce stock positions

Range of use:

- Basic industrial applications without automation

| DN (mm) | Size (inch) | PN (bar) | EPDM Code | SP | Weight (kg) | FKM Code |
|------------|----------------|-------------|--------------|----|----------------|-------------|
| 15 | ½ | 16 | 163 375 002 | 1 | 0.175 | 163 375 017 |
| 20 | ¾ | 16 | 163 375 003 | 1 | 0.269 | 163 375 018 |
| 25 | 1 | 16 | 163 375 004 | 1 | 0.389 | 163 375 019 |
| 32 | 1 ¼ | 16 | 163 375 005 | 1 | 0.568 | 163 375 020 |
| 40 | 1 ½ | 16 | 163 375 006 | 1 | 0.928 | 163 375 021 |
| 50 | 2 | 16 | 163 375 007 | 1 | 1.550 | 163 375 022 |
| 65 | 2 ½ | 10 | 163 375 008 | 1 | 2.190 | 163 375 023 |
| 80 | 3 | 10 | 163 375 009 | 1 | 3.360 | 163 375 024 |
| 100 | 4 | 10 | 163 375 010 | 1 | 6.060 | 163 375 025 |

| D (mm) | H (mm) | L (mm) | L1 (mm) | L2 (mm) | L3 (mm) | z (mm) |
|-----------|-----------|-----------|------------|------------|------------|-----------|
| 50 | 53 | 79 | 67 | 42 | 40 | 48 |
| 59 | 60 | 92 | 77 | 48 | 45 | 53 |
| 68 | 67 | 105 | 87 | 54 | 51 | 58 |
| 80 | 79 | 120 | 102 | 62 | 59 | 68 |
| 94 | 90 | 126 | 119 | 72 | 70 | 78 |
| 115 | 107 | 150 | 146 | 86 | 84 | 93 |
| 145 | 129 | 206 | 179 | 110 | 103 | 118 |
| 168 | 143 | 242 | 209 | 128 | 120 | 140 |
| 210 | 169 | 282 | 250 | 150 | 141 | 160 |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:

info.ps@georgfischer.com Internet: <http://www.gfps.com>