



SYGEF Plus instrument installation fitting SDR33/PN10
High Purity clean-room product ISO Class 5 (100)

Model:

- Material: PVDF-HP
- Suitable for hole diameters from 1/8" - 3/4"
- Machined version

Range of use:

- compatible with all signet sensors excepting flow sensors

Note:

Hole needs to be milled, HAND HELD DRILLING MUST NOT BE DONE

* no stock item

	d	DN	PN	SDR	FM	Code	Weight	D	e	H	L	L1	L2
	(mm)	(mm)	(bar)				(kg)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
*	125	100	10	33	IR	735 918 565	0.858	162	3.9	157	100	40	27
*	140	125	10	33	IR	735 918 566	1.119	176	4.4	171	110	40	32
*	160	150	10	33	IR	735 918 567	1.151	194	4.9	190	110	40	32
*	125	100	10	33	IR	735 918 569	1.486	231	6.2	228	110	40	32
*	225	200	10	33	IR	735 918 570	1.862	254	7.0	251	110	40	32

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
 info.ps@georgfischer.com Internet: <http://www.gfps.com>