





PROGEF Plus silicone free Diaphragm valve type 514
With butt fusion spigots SDR11 metric

Model:

- Material: PP-H / silicone free cleaned
- Double flow rate compared to predecessor
- One housing nut replaces four screws
- Handwheel with built-in locking mechanism
- For easy installation and removal
- Short overall length

Option:

- Individual configuration of the valve
- Self adjusting multifunctional module with integrated limit switches

* O-Ring material: FKM

d (mm)	DN (mm)	Size (inch)	PN (bar)	kv-value ($\Delta p=1$ bar) (l/min)	EPDM Code	PTFE/ EPDM* Code	GP	Weight (kg)
20	15	½	10	125	167 514 122	167 514 172		0.274
25	20	¾	10	271	167 514 123	167 514 173		0.404
32	25	1	10	481	167 514 124	167 514 174		0.652
40	32	1 ¼	10	759	167 514 125	167 514 175		0.853
50	40	1 ½	10	1263	167 514 126	167 514 176		1.453
63	50	2	10	1728	167 514 127	167 514 177		3.072

d (mm)	D (mm)	D2 (mm)	D3 (mm)	H (mm)	H1 (mm)	H2 (mm)	L (mm)	L2 (mm)	M	e (mm)	Lift = Hx (mm)	closest inch (inch)
20	65	65	43	73	14	12	196	25	M6	1.9	7	½
25	80	65	51	81	18	12	221	25	M6	2.3	10	¾
32	88	87	58	107	22	12	234	25	M6	2.9	13	1
40	101	87	72	115	26	15	260	45	M8	3.7	15	1 ¼
50	117	135	83	148	32	15	284	45	M8	4.6	19	1 ½
63	144	135	100	166	39	15	321	45	M8	5.8	25	2

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
 info.ps@georgfischer.com Internet: <http://www.gfps.com>