



Uni/Fleks ring

Model:

- Consists of a segmented plastic ring and Varioseal (gasket)
- EPDM gasket, EPDM acc. to EN 681-1 (0°C up to +50°C)
- non-restraint

DN (mm)	Range (mm)	NBR Code	EPDM Code	weight (kg)
50	46 - 71	709 390 030	709 390 130	0.192
65	63 - 90	709 390 032	709 390 132	0.232
80	84 - 105	709 390 034	709 390 134	0.267
100	104 - 132	709 390 036	709 390 136	0.001
125	132 - 155	709 390 038	709 390 138	0.627
150	154 - 192	709 390 040	709 390 140	0.838
200	192 - 232	709 390 043	709 390 143	0.987
225	230 - 268	709 390 046	709 390 146	1.100
250	267 - 310	709 390 048	709 390 148	1.300
300	315 - 356	709 390 053	709 390 153	1.700
350	352 - 393	709 390 054	709 390 154	2.000
400	392 - 433	709 390 056	709 390 156	2.200
425	432 - 464	709 390 082	709 390 182	4.000
450	450 - 482	709 390 078	709 390 178	2.400
475	481 - 513	709 390 083	709 390 183	4.400
500	500 - 532	709 390 079	709 390 179	2.600
550	548 - 580	709 390 080	709 390 180	2.800
600	605 - 637	709 390 081	709 390 181	3.000

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>