



Installation fitting type 314 PVC-U metric

Model:

- Threaded outlet 1 1/4" NPSM
- for conventional hot gas back welding according to DVS 2207 part 3

Attention:

- only for pressureless or low pressure application
- pressure rate depends on quality of hot gas back welding
- please consult the instruction manual
- Installation by trained and certified welders only
- sensor length depends on installation fitting

Range of use:

- compatible signet flow sensors: type 2551, 2537, 515, 8510, 2536, 8512
- compatible signet pH/ORP sensors: type 2724, 2725, 2726

DN	d (mm)	PN* (bar)	Code	SP	Weight (kg)	Sensor Type	D (mm)	L (mm)
65 - 150	75 - 180	-	721 314 000	1	0.053	flow X0, pH XX	38	68
200 - 350	200 - 355	-	721 314 001	1	0.078	flow X1	38	102
350 - 600	400 - 630	-	721 314 002	1	0.153	flow X2	38	178

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>