





NeoFlow Pressure Sustaining Valve POM-C DN50 - DN150 / Set pressure range 1 - 16 bar


- Nominal pressure: PN16
- Connection type: Wafer Design
- Sealing material: EPDM
- Body material: POM-C
- Components: Stainless Steel
- Thread fittings: BSP
- Medium: Water
- Co-developed with OFUI



d (mm)	DN	PN	Set pressure range (bar)	Body	Code	Weight (kg)
63	50	16	1.0 - 16.0	POM-C	193 176 211	57.0
90	80	16	1.0 - 16.0	POM-C	193 176 213	66.0
110	100	16	1.0 - 16.0	POM-C	193 176 214	79.0
160	150	16	1.0 - 16.0	POM-C	193 176 217	131.0



D (mm)	Lmax (mm)	Lb (mm)	Hmax (mm)	Wmax (mm)
105	266	121	290	275
134	289	135	310	295
162	287	155	340	310
218	289	230	395	355



The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>