



JRGUMAT Thermostatic mixing valve gunmetal

- Temperature: max. 90°C
- Factory setting: 25 / 40 / 48 / 55 / 70°C (adjustable)
- Material: gunmetal
- Connection: male thread
- Thread type d2 = G
- Thread type d3 = G

DN (mm)	Thread Type	Size (inch)	min Tempera- ture (°C)	max Temper- ature (°C)	Temperature (°C)	JRG Code
15	GN	½	20	30	25	3400.910
15	GN	½	30	45	40	3400.912
15	GN	½	45	65	55	3400.916
15	GN	½	60	80	70	3400.918
20	GN	¾	20	30	25	3400.920
20	GN	¾	30	45	40	3400.922
20	GN	¾	45	65	55	3400.926
20	GN	¾	60	80	70	3400.928
25	GN	1	20	30	25	3400.930
25	GN	1	30	45	40	3400.932
25	GN	1	45	65	55	3400.936
25	GN	1	60	80	70	3400.938
32	GN	1 ¼	20	30	25	3400.940
32	GN	1 ¼	30	45	40	3400.942
32	GN	1 ¼	45	65	55	3400.946
32	GN	1 ¼	60	80	70	3400.948
40	GN	1 ½	20	30	25	3400.950
40	GN	1 ½	30	45	40	3400.952
40	GN	1 ½	45	65	55	3400.956
40	GN	1 ½	60	80	70	3400.958
50	GN	2	20	30	25	3400.960
50	GN	2	30	45	40	3400.962
50	GN	2	45	65	55	3400.966
50	GN	2	60	80	70	3400.968

DN (mm)	Thread Type	GF Code	SP	Weight (kg)
15	GN	350 760 511	1	0.530
15	GN	350 760 512	1	0.530
15	GN	350 760 513	1	0.530
15	GN	350 760 514	1	0.530
20	GN	350 760 411	1	0.700
20	GN	350 760 412	1	0.670
20	GN	350 760 413	1	0.701
20	GN	350 760 414	1	0.701
25	GN	350 760 311	1	0.870
25	GN	350 760 312	1	0.870
25	GN	350 760 313	1	0.910
25	GN	350 760 314	1	0.910
32	GN	350 760 211	1	1.670
32	GN	350 760 212	1	1.630
32	GN	350 760 213	1	1.590
32	GN	350 760 214	1	1.590
40	GN	350 760 111	1	2.140
40	GN	350 760 112	1	2.140
40	GN	350 760 113	1	2.100
40	GN	350 760 114	1	2.100

DN (mm)	Thread Type	GF Code	SP	Weight (kg)
50	GN	350 760 011	1	3.610
50	GN	350 760 012	1	3.510
50	GN	350 760 013	1	3.510
50	GN	350 760 014	1	3.510

DN (mm)	Thread Type	d2 (inch)	d3 (inch)	h1 (mm)	h2 (mm)	h3 (mm)	l (mm)	l1 (mm)	l2 (mm)	PN (bar)	⬡ (mm)
15	GN	1 1/8			47	35	90	35	55	10	5
15	GN	1 1/8			47	35	90	35	55	10	5
15	GN	1 1/8			47	35	90	35	55	10	5
15	GN	1 1/8			47	35	90	35	55	10	5
20	GN	1 1/4	1/2	32	49	40	100	40	60	10	5
20	GN	1 1/4	1/2	32	49	40	100	40	60	10	5
20	GN	1 1/4	1/2	32	49	40	100	40	60	10	5
20	GN	1 1/4	1/2	32	49	40	100	40	60	10	5
25	GN	1 1/2	3/4	36	51	43	110	43	67	10	5
25	GN	1 1/2	3/4	36	51	43	110	43	67	10	5
25	GN	1 1/2	3/4	36	51	43	110	43	67	10	5
25	GN	1 1/2	3/4	36	51	43	110	43	67	10	5
32	GN	2	3/4	41	75	52	130	52	78	10	8
32	GN	2	3/4	41	75	52	130	52	78	10	8
32	GN	2	3/4	41	75	52	130	52	78	10	8
32	GN	2	3/4	41	75	52	130	52	78	10	8
40	GN	2 1/4	3/4	50	77	58	150	58	92	10	8
40	GN	2 1/4	3/4	50	77	58	150	58	92	10	8
40	GN	2 1/4	3/4	50	77	58	150	58	92	10	8
40	GN	2 1/4	3/4	50	77	58	150	58	92	10	8
50	GN	2 3/4	3/4	60	85	70	180	70	110	10	8
50	GN	2 3/4	3/4	60	85	70	180	70	110	10	8
50	GN	2 3/4	3/4	60	85	70	180	70	110	10	8
50	GN	2 3/4	3/4	60	85	70	180	70	110	10	8

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>