





Tapping saddle d40-63 Monobloc version

- 10 bar Gas / 16 bar Water
- With integrated cutter to tap live mains under pressure
- Complete with lower part
- 4mm pin connectors
- Limited path fusion indicators
- Long fusion outlet
- O-ring-sealed screw cap



d	Do3	DN	PN	Code	Weight	L	L4	Db	W	H	H4	SDR pipe
(mm)	(mm)	(mm)	(bar)		(kg)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	
40	20	32	16	193 131 412	0.225	102	70	16	103	99	33	9 - 11
40	25	32	16	193 131 413	0.226	102	70	16	103	99	33	9 - 11
40	32	32	16	193 131 414	0.225	120	70	16	103	99	33	9 - 11
50	20	40	16	193 131 422	0.214	102	70	16	103	104	38	9 - 11
50	25	40	16	193 131 423	0.212	102	70	16	103	104	38	9 - 11
50	32	40	16	193 131 424	0.228	120	70	16	103	104	38	9 - 11
63	32	50	16	193 131 434	0.425	130	70	25	126	134	44	9 - 17.6

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>