




Lug-Style, end installation butterfly valve metal type 038
With electric actuator 230V
Flange standard metric - PN10
Disc: stainless steel DIN Norm 1.4408 without coating

Model:

- Lug Style
- Body GGG40 (A 395 / A395 M-99, EN-JIS 1020 EN1563) Rilsan® coating
- Installation length: EN 558 row 20
- Interface according to DIN EN ISO 5211
- Pressure range: 10 bar (DN 50-200); 6 bar (DN 250); 4 bar (DN 300 - 600)
- Axis DN50 - DN300: Single-piece axis with square profile, material stainless steel DIN Norm 1.4021
- Flange connection: DN50 - DN300: PN6, PN10, ANSI 125/150 Lbs., BS 10-D/E
- Voltage 100-230V, 50-60Hz for EA actuator

Option:

- Other liner material on request
- Optional accessories: Fail-safe return unit



d (mm)	DN (mm)	Size (inch)	PN (bar)	kv-value ($\Delta p=1$ bar) (l/min)	Liner: EPDM Code	PF	SP	Weight (kg)
63	50	2	10	3140	199 038 330	3 39 226 103	1	5.40
75	65	2 ½	10	4570	199 038 331	3 39 226 103	1	6.50
90	80	3	10	7140	199 038 332	3 39 226 103	1	9.60
110	100	4	10	11710	199 038 333	3 39 226 103	1	11.60
140	125	5	10	18570	199 038 334	3 39 226 103	1	18.98
160	150	6	10	27130	199 038 335	3 39 226 103	1	16.50
225	200	8	10	47130	199 038 336	3 39 226 103	1	23.30
*	280	250	10	77110	199 038 337	3 39 226 103	1	36.50
*	315	300	12	114240	199 038 338	3 39 226 103	1	53.30

d (mm)	Liner: FKM Code	Liner: EPDM DVGW Code	Liner: NBR Code
63	199 038 787	199 038 749	199 038 769
75	199 038 788	199 038 750	199 038 770
90	199 038 789	199 038 751	199 038 771
110	199 038 790	199 038 752	199 038 772
140	199 038 791	199 038 753	199 038 773
160	199 038 792	199 038 754	199 038 774
225	199 038 793	199 038 755	199 038 775
*	280	199 038 756	199 038 776
*	315	199 038 757	199 038 777

d (mm)	Type of actuator	H (mm)	H1 (mm)	H2 (mm)	H3 (mm)	L (mm)	L1 (mm)	L2 (mm)
63	EA45	393	63	140	188	43	28	122
75	EA120	415	73	152	188	46	28	122
90	EA120	430	81	159	188	46	28	122
110	EA120	333	97	178	188	52	60	220
140	EA120	361	112	191	188	56	60	220
160	EA250	383	122	203	208	56	60	220
225	EA250	452	149	245	208	60	60	220
*	EA250	545	203	275	208	68	70	220
*	EA250	623	241	315	208	78	70	220

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Data sheet

valid from: 12/13/24



Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>