



ecoFIT Segmented Bend 1.5D 45° PE100 SDR11

Model:

- Long spigot for butt- and electrofusion welding
- Production process: segment welded
- Application: Water distribution
- **Derating factor 0.8 as per ISO 4427-3**
- Pressure rating: 12.8 bar water

Note:

* Please call us for availability

d	Code	Weight	Z	L	R	e	
(mm)		(kg)	(mm)	(mm)	(mm)	(mm)	
90	P2316605090	0.97	232	150	198.0	8.2	
110	P2316605110	1.82	291	200	220.0	10.0	
125	P2316605125	2.41	293	200	225.0	11.4	
140	P2316605140	3.00	293	200	224.0	12.7	
160	P2316605160	4.01	299	200	240.0	16.6	
180	P2316605180	5.23	312	200	270.0	16.4	
200	P2316605200	6.77	324	200	300.0	18.2	
225	P2316605225	8.97	340	200	337.5	20.5	
250	P2316605250	13.18	405	250	375.0	22.7	
280	P2316605280	17.13	424	250	420.0	25.4	
315	P2316605315	27.96	546	350	472.5	28.6	
355	P2316605355	37.14	571	350	532.5	32.2	
400	P2316605400	46.69	599	350	600.0	36.3	
450	P2316605450	66.12	630	350	675.0	40.9	
500	P2316605500	92.11	711	400	750.0	45.4	
560	P2316605560	121.16	748	400	840.0	50.8	
630	P2316605630	172.31	841	450	945.0	57.2	
710	P2316605710	245.42	941	500	1065.0	64.5	
*	800	P2316605800	378.27	1167	650	1200.0	72.6
*	900	P2316605900	525.99	1259	700	1350.0	81.7

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:

info.ps@georgfischer.com Internet: <http://www.gfps.com>