



UNI-Combigrip S/S2/S3/S4 coupling stainless steel 1.4571
Tensile-resistant connection of metal and plastic
PN2,5 Solid bolt

Model:

- Housing, Bars and Strip insert (option): Stainless Steel W5 (1.4571) Quality

Temperature/Pressure:

- Operating temperature EPDM: -30°C to 125°C
- Operating temperature NBR: -20°C to 80°C

Option:

- Sealing type Viton (FKM) on request

Remark:

For safe installation on PVC-, ABS-, PE-, PP- and PB-pipes insert stiffeners are mandatory

Attention:

- The difference between the different pipe outside diameters OD1 < OD2 is 1% or max. 3 mm.

OD nominal (mm) (mm)	EPDM Code	PF	NBR Code	PF Weight (kg)
312 - 325	779 760 929	1 D1 A90 130	779 757 929	1 D1 A90 230 7.8
350 - 363	779 760 930	1 D1 A90 130	779 757 930	1 D1 A90 230 8.5
395 - 408	779 760 931	1 D1 A90 130	779 757 931	1 D1 A90 230 10.5
447 - 460	779 760 932	1 D1 A90 130	779 757 932	1 D1 A90 230 13.1
502 - 515	779 760 933	1 D1 A90 130	779 757 933	1 D1 A90 230 14.5
557 - 570	779 760 934	1 D1 A90 130	779 757 934	1 D1 A90 230 21.1
627 - 640	779 760 935	1 D1 A90 130	779 757 935	1 D1 A90 230 23.5

OD nominal (mm) (mm)	PN (bar)	WP (bar)	OD min (mm)	OD max. (mm)	d (mm)	B (mm)	H (mm)	Torque maxi- mal (N/m)
312 - 325	2.5	6	312	325	363	140	389	160
350 - 363	2.5	6	350	363	401	140	427	160
395 - 408	2.5	6	395	408	446	142	472	160
447 - 460	2.5	6	447	460	498	142	524	160
502 - 515	2.5	6	502	515	553	142	579	160
557 - 570	2.5	6	557	570	608	146	634	160
627 - 640	2.5	6	627	640	678	146	704	160

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
 info.ps@georgfischer.com Internet: <http://www.gfps.com>