



PROGEF Standard Ball valve type 127
24V
With manual emergency override
With socket fusion spigots PP-H ISO

Model:

- IP68 Rating
- Factory set control range 90°<
- Heating element, position feedback (Open/Close)
- Integrated stainless steel mounting inserts

Option:

- Other valve and actuator configurations available
- Optional accessories: Fail-safe return unit

d	DN	Size	PN	kv-value	EPDM	Weight	FKM	Weight
(mm)	(mm)	(inch)	(bar)	($\Delta p=1$ bar)	Code	(kg)	Code	(kg)
				(l/min)				
16	10	3/8	10	70	199 127 562	2.100	199 127 572	2.100
20	15	1/2	10	185	199 127 563	2.100	199 127 573	2.096
25	20	3/4	10	350	199 127 564	2.200	199 127 574	2.200
32	25	1	10	700	199 127 565	2.245	199 127 575	2.300
40	32	1 1/4	10	1000	199 127 566	2.600	199 127 576	2.600
50	40	1 1/2	10	1600	199 127 567	3.000	199 127 577	3.000
63	50	2	10	3100	199 127 568	3.800	199 127 578	3.800

d	Actuator	B3	DE1	E	G	H	H1	H4	L	L1	Lz	M	M1	M2	s1
(mm)		(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
16	EA15	25	50	122	M6	197	27	12	110	33	28	161	77	83	3.0
20	EA15	25	50	122	M6	197	27	12	120	33	28	161	77	83	3.0
25	EA15	25	58	122	M6	201	30	12	139	33	33	161	77	83	3.0
32	EA15	25	68	122	M6	207	36	12	150	33	36	161	77	83	4.0
40	EA15	45	84	122	M8	213	44	15	170	33	43	161	77	83	4.5
50	EA15	45	97	122	M8	219	51	15	190	33	45	161	77	83	5.5
63	EA15	45	124	122	M8	234	64	15	220	33	51	161	77	83	7.0

d	z
(mm)	(mm)
16	84
20	92
25	107
32	114
40	130
50	144
63	166

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>