




SYGEF 标准型
546 Pro 球阀
带钢衬PP支撑法兰 美标

型号:


- PTFE球密封
- 内置不锈钢固定螺孔
- Z尺寸、阀端和活接螺母与546型球阀（第1代）兼容

选项:

- Interface module for position feedback sensor with LED (PNP, NPN and NAMUR)
- Manual spring return lever "Dead man" (DN10-25)
- 可配GF气动或电动执行器
- Individual configuration of valves possible



d	DN	Inch	PN	kv-value	FKM	weight
(mm)	(mm)	(inch)	(bar)	($\Delta p=1$ bar)	code	(kg)
				(l/min)		
75	65	2 1/2	16	5000	175 546 818	11,700
90	80	3	16	7000	175 546 819	16,000
110	100	4	16	11000	175 546 820	23,900



b1	B3	DE1	G	H	H1	H4	k1	L	Lz	M	M1	M2
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
18	70	166	M8	234	85	15	140	290	68	270	64	206
20	70	200	M8	234	105	15	150	310	71	270	64	206
20	120	238	M12	234	123	22	175	350	82	320	64	206

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: <http://www.gfps.com>