



Colliers de prise avec robinet, Kit Système P - Perforateur avec départ orientable sur 360°



- 5 bar gaz / 16 bar eau
- Avec perforateur incorporé pour perforer des tubes sous pression
- **Ne convient que pour les tubes avec une épaisseur de paroi comprise entre 7 et 21 mm.**
- Complet avec corps et vanne prémontée (PE 100 couvert par extrusion)
- Le robinet se ferme dans le sens des aiguilles d'une montre
- Le nombre de tours pour ouvrir ou fermer complètement la vanne est de 13 pour sortie d32
- Number of turns to fully open or close valve is 28 for outlet d40, d50, d63
- Carré de la tige (SW) 14
- Connecteurs 4 mm
- Indicateur de soudage
- Sortie à bout lisse
- livré en kit avec réduction ou manchon ELGEF® Plus

* Livraison sans selle inférieure, pour assembleate Top Load avec outil 799.350.477; adaptateur de prise coudé (799.350.340) nécessaire

d	Do3	DN	PN	Code	CAN	Poids
(mm)	(mm)	(mm)	(bar)			(kg)
250	32	250	16	193 155 134		3.443
280	32	250	16	193 155 148		3.118
280	40	250	16	193 155 149		2.913
280	50	250	16	193 155 150		3.136
280	63	250	16	193 155 151		2.719
315	32	300	16	193 155 158		3.118
315	40	300	16	193 155 159		3.124
315	50	300	16	193 155 160		3.136
315	63	300	16	193 155 161		3.134
*	355	32	350	193 155 154		3.118
*	355	40	350	193 155 155		3.124
*	355	50	350	193 155 156		3.136
*	355	63	350	193 155 157		3.134

d	Do3	L	L4	Db	W	H	H4	Tube SDR
(mm)								
250	32	127	70	21	164	293	191	17 - 26
280	32	127	70	21	164	293	191	17 - 26
280	40	160	100	31	164	366	206	17 - 26
280	50	160	100	31	164	366	206	17 - 26
280	63	160	100	31	164	366	206	17 - 26
315	32	127	70	21	164	293	191	17 - 33
315	40	160	100	31	164	366	206	17 - 33
315	50	160	100	31	164	366	206	17 - 33
315	63	160	100	31	164	366	206	17 - 33
*	355	127	70	21	165	293	191	17 - 33
*	355	160	100	31	165	366	206	17 - 33
*	355	160	100	31	165	366	206	17 - 33
*	355	160	100	31	165	366	206	17 - 33

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>