



ecoFIT Segmented Bend 1.5D 60° PE100 SDR17

Model:

- Long spigot for butt- and electrofusion welding
- Production process: segment welded
- Application: Water distribution
- **Derating factor 0.8 as per ISO 4427-3**
- Pressure rating: 8 bar water

Note:

* Please call us for availability

d	Code	Weight	Z	L	R	e
(mm)		(kg)	(mm)	(mm)	(mm)	(mm)
90	P2314606090	0.66	228	150	135.0	5.4
110	P2314606110	1.05	245	150	165.0	6.6
125	P2314606125	1.41	259	150	187.5	7.4
140	P2314606140	1.85	271	150	210.0	8.3
160	P2314606160	2.56	289	150	240.0	9.5
180	P2314606180	4.58	406	250	270.0	10.7
200	P2314606200	5.89	423	250	300.0	11.9
225	P2314606225	7.84	445	250	337.5	13.4
250	P2314606250	10.05	467	250	375.0	14.8
280	P2314606280	13.30	492	250	420.0	16.6
315	P2314606315	19.63	573	300	472.5	18.7
355	P2314606355	30.96	708	400	532.5	21.1
400	P2314606400	41.13	746	400	600.0	23.7
450	P2314606450	55.05	790	400	675.0	26.7
500	P2314606500	71.36	833	400	750.0	29.7
560	P2314606560	95.03	885	400	840.0	33.2
630	P2314606630	128.05	946	400	945.0	37.4
710	P2314606710	210.29	1215	600	1065.0	42.1
800	P2314606800	283.29	1293	600	1200.0	47.4
900	P2314606900	382.70	1379	700	1350.0	53.3
1000	P2314606001	500.08	1466	700	1500.0	59.3
*	P2314606002	853.25	1739	700	1800.0	71.1

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>