




## Adaptateur à bride COOL-FIT 2.0/4.0

### Exécution:

- PE100 SDR11, metric
- Suitable for flange connections to metric and/or ANSI/ASME B16.5
- Type1 sans chanfrein, Type2 avec chanfrein
- Profile flange gasket EPDM: metric No. 48 44 07, ANSI No. 48 44 05.
- Separate Fittings type A needed for joining

### Remarque:

Backing ring and gasket not included



| d<br>(mm) | DN<br>(mm) | SDR | PN | Type | Code        | poids<br>(kg) |
|-----------|------------|-----|----|------|-------------|---------------|
| 32        | 25         | 11  | 16 | 1    | 738 710 008 | 0,320         |
| 32        | 25         | 11  | 16 | 1    | 738 710 108 | 0,320         |
| 40        | 32         | 11  | 16 | 1    | 738 710 009 | 0,480         |
| 40        | 32         | 11  | 16 | 1    | 738 710 109 | 0,480         |
| 50        | 40         | 11  | 16 | 1    | 738 710 010 | 0,620         |
| 63        | 50         | 11  | 16 | 1    | 738 710 011 | 0,910         |
| 50        | 40         | 11  | 16 | 1    | 738 710 110 | 0,620         |
| 75        | 65         | 11  | 16 | 2    | 738 710 012 | 1,220         |
| 90        | 80         | 11  | 16 | 2    | 738 710 013 | 1,650         |
| 90        | 80         | 11  | 16 | 2    | 738 710 113 | 1,650         |
| 110       | 100        | 11  | 16 | 2    | 738 710 014 | 2,390         |
| 140       | 125        | 11  | 16 | 2    | 738 710 016 | 3,660         |
| 160       | 150        | 11  | 16 | 2    | 738 710 017 | 4,800         |
| 225       | 200        | 11  | 16 | 2    | 738 710 020 | 9,600         |

| d<br>(mm) | D<br>(mm) | d1<br>(mm) | D1<br>(mm) | d2<br>(mm) | D2<br>(mm) | d3<br>(mm) | d4<br>(mm) | d5<br>(mm) | L<br>(mm) | L1<br>(mm) | L2<br>(mm) | L3<br>(mm) | Standard     | z<br>(mm) |
|-----------|-----------|------------|------------|------------|------------|------------|------------|------------|-----------|------------|------------|------------|--------------|-----------|
| 32        | 135       | 40         | 90         | 68         |            |            | 26         | 121        | 162       | 36         | 10         | 26         | Metric       | 190       |
| 32        | 135       | 40         | 90         | 63         | 63         |            | 26         | 121        | 162       | 36         | 10         | 26         | ANSI         | 190       |
| 40        | 170       | 50         | 110        | 78         | 90         |            | 32         | 146        | 165       | 40         | 11         | 28         | Metric       | 197       |
| 40        | 170       | 50         | 110        | 73         | 73         |            | 32         | 146        | 165       | 40         | 11         | 28         | ANSI         | 197       |
| 50        | 180       | 61         | 110        | 88         | 90         |            | 40         | 156        | 178       | 44         | 12         | 30         | Metric       | 214       |
| 63        | 200       | 75         | 125        | 102        | 110        |            | 51         | 171        | 230       | 48         | 14         | 32         | Metric, ANSI | 270       |
| 50        | 180       | 61         | 110        | 82         | 82         |            | 40         | 156        | 178       | 44         | 12         | 30         | ANSI         | 214       |
| 75        | 220       | 89         | 140        | 122        | 125        | 66         | 61         | 191        | 232       | 55         | 16         | 34         | Metric, ANSI | 279       |
| 90        | 240       | 105        | 160        | 138        | 140        | 78         | 73         | 206        | 245       | 62         | 17         | 35         | Metric       | 299       |
| 90        | 240       | 105        | 160        | 133        | 133        | 78         | 73         | 206        | 245       | 62         | 17         | 35         | ANSI         | 299       |
| 110       | 270       | 125        | 180        | 158        | 160        | 100        | 90         | 235        | 254       | 72         | 18         | 36         | Metric, ANSI | 320       |
| 140       | 300       | 155        | 225        | 188        | 200        | 127        | 127        | 256        | 299       | 84         | 25         | 38         | Metric, ANSI | 383       |
| 160       | 358       | 174        | 259        | 213        | 213        | 151        | 131        | 295        | 332       | 90         | 25         | 34         | Metric, ANSI | 412       |
| 225       | 423       | 233        | 325        | 268        | 268        | 209        | 184        | 354        | 383       | 110        | 32         | 37         | Metric, ANSI | 483       |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>