



IR PVC-U Coudes 45°



Exécution:

- Pour le soudage sur IR-63 Plus et IR-110 A
- Inserts de serrage spéciaux nécessaires pour IR-63 Plus et IR-110 A
- Utiliser uniquement le nettoyant Tangit KS (799298023)



d	DN	PN	SDR	Code	CAN	Poids	CAN	s	Bm1	z
(mm)	(mm)	(bar)				(kg)		(mm)	(mm)	(mm)
20	15	16	9	721 158 106		0.014		2.3	21	32
25	20	16	13.6	721 158 107		0.017		1.9	21	34
32	25	16	13.6	721 158 108		0.028		2.4	21	36
40	32	16	13.6	721 158 109		0.046		3.0	21	39
50	40	16	13.6	721 158 110		0.086		3.7	21	42
63	50	16	13.6	721 158 111		0.134		4.7	25	47

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: <http://www.gfps.com>