

UNI-Grip S / SE Kupplung Edelstahl 1.4571 Zugfeste Verbindung von Metall und Metall PN10 Vollbolzen

Ausführung:

- Gehäuse, Schrauben und Bänderinlage (optional): Edelstahl 1.4571 (W5)

Temperatur-/Druck:

- Temperaturbereich EPDM: -30°C bis 125°C
- Temperaturbereich NBR: -20°C bis 80°C

Option:



- Dichtwerkstoff Viton (FKM) auf Anfrage
- *Es gelten eingeschränkte Verwendungsbedingungen für CuNiFe Rohre mit einer Wandstärke ≤ 4 mm. Die mit einem Stern versehenen Rohrdimensionen dürfen nur mit max. PN 2.5 belastet werden.

Achtung:

- Die Differenz der unterschiedlichen Rohraussendurchmesser $OD1 < OD2$ beträgt 1% oder max. 3 mm.

	OD nominal (mm)	EPDM Code	NBR Code	Gewicht (kg)
	64 - 72	779 724 411	779 721 411	1.0
	72 - 80	779 724 412	779 721 412	1.0
	80 - 88	779 724 413	779 721 413	1.0
	88 - 96	779 724 414	779 721 414	1.0
	97 - 105	779 724 415	779 721 415	1.1
	104 - 112	779 724 416	779 721 416	1.1
	112 - 120	779 724 417	779 721 417	1.2
	122 - 130	779 724 418	779 721 418	1.2
	129 - 137	779 724 419	779 721 419	2.1
	137 - 145	779 724 420	779 721 420	2.2
	149 - 157	779 724 421	779 721 421	2.3
	157 - 165	779 724 422	779 721 422	2.3
	164 - 172	779 724 423	779 721 423	2.4
	210 - 223	779 764 126	779 762 126	6.9
	221 - 234	779 764 127	779 762 127	7.0
	234 - 247	779 764 128	779 762 128	7.2
	247 - 260	779 764 129	779 762 129	7.5
*	263 - 276	779 764 130	779 762 130	7.7
*	277 - 290	779 764 131	779 762 131	7.9
*	288 - 301	779 764 132	779 762 132	11.1
*	301 - 314	779 764 133	779 762 133	11.5
*	315 - 328	779 764 134	779 762 134	11.8
*	327 - 340	779 764 135	779 762 135	12.1
*	340 - 353	779 764 136	779 762 136	12.4
*	350 - 363	779 764 137	779 762 137	12.7
*	361 - 374	779 764 138	779 762 138	13.0

OD nominal (mm)	PN (bar)	WP (bar)	OD min (mm)	OD max. (mm)	d (mm)	B (mm)	H (mm)
64 - 72	10	16	64	72	108	95	164
72 - 80	10	16	72	80	108	95	164
80 - 88	10	16	80	88	124	95	170
88 - 96	10	16	88	96	124	95	170
97 - 105	10	16	97	105	141	95	187
104 - 112	10	16	104	112	141	95	187
112 - 120	10	16	112	120	158	95	202
122 - 130	10	16	122	130	158	95	202
129 - 137	10	16	129	137	178	110	230
137 - 145	10	16	137	145	186	110	238



OD nominal (mm) (mm)	PN (bar)	WP (bar)	OD min (mm)	OD max. (mm)	d (mm)	B (mm)	H (mm)
149 - 157	10	16	149	157	197	110	249
157 - 165	10	16	157	165	205	110	255
164 - 172	10	16	164	172	212	110	262
210 - 223	10	16	210	223	261	138	287
221 - 234	10	16	221	234	272	138	298
234 - 247	10	16	234	247	285	138	311
247 - 260	10	16	247	260	298	138	324
* 263 - 276	10	16	263	276	314	138	340
* 277 - 290	10	16	277	290	328	140	354
* 288 - 301	10	16	288	301	339	140	365
* 301 - 314	10	16	301	314	352	140	378
* 315 - 328	10	16	315	328	366	140	392
* 327 - 340	10	16	327	340	378	140	404
* 340 - 353	10	16	340	353	391	140	417
* 350 - 363	10	16	350	363	401	140	427
* 361 - 374	10	16	361	374	412	142	438

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>