

UNI-Grip S coupling stainless steel 1.4571
Tensile-resistant connection of metal and metal
PN2,5 Solid bolt

Model:

- Housing, Bars and Strip insert (option): Stainless Steel W5 (1.4571) Quality

Temperature/Pressure:

- Operating temperature EPDM: -30°C to 125°C
- Operating temperature NBR: -20°C to 80°C

Option:

- Sealing type Viton (FKM) on request

Attention:



- The difference between the different pipe outside diameters OD1<OD2 is 1% or max. 3 mm.

OD nominal (mm)	EPDM Code	NBR Code	Weight (kg)
288 - 301	779 764 332	779 762 332	6.8
301 - 314	779 764 333	779 762 333	7.0
315 - 328	779 764 334	779 762 334	7.2
327 - 340	779 764 335	779 762 335	7.4
340 - 353	779 764 336	779 762 336	7.5
350 - 363	779 764 337	779 762 337	7.7
361 - 374	779 764 338	779 762 338	7.8
374 - 387	779 764 339	779 762 339	9.5
387 - 400	779 764 340	779 762 340	9.7
400 - 413	779 764 341	779 762 341	9.9
412 - 425	779 764 342	779 762 342	10.1
422 - 435	779 764 343	779 762 343	10.3
438 - 451	779 764 344	779 762 344	10.5
451 - 464	779 764 345	779 762 345	10.7
460 - 473	779 764 346	779 762 346	10.9
476 - 489	779 764 347	779 762 347	11.1
488 - 501	779 764 348	779 762 348	11.3
503 - 516	779 764 349	779 762 349	11.6
520 - 533	779 764 350	779 762 350	16.9
531 - 544	779 764 351	779 762 351	17.2
546 - 559	779 764 352	779 762 352	17.6
557 - 570	779 764 353	779 762 353	17.9
571 - 584	779 764 354	779 762 354	18.2
600 - 613	779 764 355	779 762 355	18.9
610 - 623	779 764 356	779 762 356	19.2
628 - 641	779 764 357	779 762 357	19.6
648 - 661	779 764 358	779 762 358	20.1
676 - 689	779 764 359	779 762 359	20.8
688 - 701	779 764 360	779 762 360	21.1
700 - 713	779 764 361	779 762 361	21.4
717 - 730	779 764 362	779 762 362	21.9
732 - 745	779 764 363	779 762 363	22.2

OD nominal (mm)	PN (bar)	WP (bar)	OD min (mm)	OD max. (mm)	d (mm)	B (mm)	H (mm)	Torque (N/m)
288 - 301	2.5	6	288	301	339	138	365	160
301 - 314	2.5	6	301	314	352	138	378	160
315 - 328	2.5	6	315	328	366	138	392	160
327 - 340	2.5	6	327	340	378	138	404	160
340 - 353	2.5	6	340	353	391	138	417	160
350 - 363	2.5	6	350	363	401	138	427	160
361 - 374	2.5	6	361	374	412	138	438	160
374 - 387	2.5	6	374	387	425	138	451	160

Data sheet

valid from: 2/24/25



OD nominal (mm) (mm)	PN (bar)	WP (bar)	OD min (mm)	OD max. (mm)	d (mm)	B (mm)	H (mm)	Torque (N/m)
387 - 400	2.5	6	387	400	438	138	464	160
400 - 413	2.5	6	400	413	451	138	477	160
412 - 425	2.5	6	412	425	463	138	489	160
422 - 435	2.5	6	422	435	473	138	499	160
438 - 451	2.5	6	438	451	489	138	515	160
451 - 464	2.5	6	451	464	502	138	528	160
460 - 473	2.5	6	460	473	511	138	537	160
476 - 489	2.5	6	476	489	527	138	553	160
488 - 501	2.5	6	488	501	539	138	565	160
503 - 516	2.5	6	503	516	554	138	580	160
520 - 533	2.5	6	520	533	575	140	603	160
531 - 544	2.5	6	531	544	586	140	614	160
546 - 559	2.5	6	546	559	601	140	629	160
557 - 570	2.5	6	557	570	612	140	640	160
571 - 584	2.5	6	571	584	626	140	654	160
600 - 613	2.5	6	600	613	655	140	683	160
610 - 623	2.5	6	610	623	665	140	693	160
628 - 641	2.5	6	628	641	683	140	711	160
648 - 661	2.5	6	648	661	703	140	731	160
676 - 689	2.5	6	676	689	731	140	759	160
688 - 701	2.5	6	688	701	743	140	771	160
700 - 713	2.5	6	700	713	755	140	783	160
717 - 730	2.5	6	717	730	772	140	800	160
732 - 745	2.5	6	732	745	787	140	815	160

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>