



JRGURED Druckminderer Rotguss

- Temperatur: max. 70°C
- Werkstoff: Rotguss, Edelstahl, EPDM
- Auslieferungszustand: 400 kPa (4 bar)
- Sekundärdruck: 150 - 600 kPa (1.5 - 6 bar)
- *Spezialausführung auf Anfrage: 650 - 1000 kPa (6.5 - 10 bar)
- Anschluss: Flansch, Manometer

DN (mm)	JRG Code	NPK	GF Code	NPK	SP	Gewicht (kg)
65	1140.065		350 542 301	713 117	1	32.000
80	1140.080		350 542 401	713 118	1	40.000
100	1140.100		350 542 501	713 121	1	55.000

DN (mm)	d1 (mm)	d2 (mm)	h1 (mm)	h2 (mm)	l1 (mm)	l2 (mm)	PN (bar)	○
65	65	187	128	340	290	145	16	4
80	80	217	144	405	310	155	16	8
100	100	257	166	465	350	175	16	8

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>