



JRGURED Druckminderer Rotguss - neu

- Temperatur: max. 30°C
- Werkstoff: Rotguss, Edelstahl, EPDM, Kunststoff
- Auslieferungszustand: 400 kPa (4 bar)
- Sekundärdruck: 200 - 600 kPa (2 - 6 bar)
- Anschluss: Manometer
- Bestehend aus: Verschraubungen
- Gewindetyp d1 = R
- Gewindetyp d2 = G
- Gewindetyp d3 = Rp

DN	GN	Zoll	JRG	NPK	GF	NPK	SP	Gewicht
(mm)	(inch)	(inch)	Code		Code			(kg)
15	½	½	1300.240		350 740 131		1	0.700
20	¾	¾	1300.320		350 740 231		1	0.900
25	1	1	1300.400		350 740 331		1	1.600
32	1 ¼	1 ¼	1300.480		350 740 431		1	2.400
40	1 ½	1 ½	1300.560		350 740 531		1	4.050
50	2	2	1300.640		350 740 631		1	6.425
65	2 ½	2 ½	1300.720		350 740 731		1	6.951

DN	GN	d1	d2	d3	d4	h1	h2	l1	l2	z	⌀	PN
(mm)	(inch)	(inch)	(inch)	(inch)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(bar)
15	½	½	¾	½	53	34	79	130	25	40	5	25
20	¾	¾	1	½	53	42	81	142	29	43	5	25
25	1	1	1 ¼	¾	60	55	90	167	34	50	5	25
32	1 ¼	1 ¼	1 ½	¾	72	67	109	196	38	60	6	25
40	1 ½	1 ½	1 ¾	¾	80	80	122	222	39	73	6	25
50	2	2	2 ¾	¾	96	98	151	268	47	88	8	25
65	2 ½	2 ½	3	¾	96	98	151	292	56	90	8	25

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>