



JRG Soupape de retenue bronze

- Température : max. 90°C
- Matériel: bronze, acier inoxydable, EPDM, plastique
- Pression d'ouverture : < 5 kPa (< 50 mbar)
- Raccord: Filetage intérieur

DN (mm)	GN (inch)	Pouces (inch)	JRG Code	CAN	GF Code	CAN	SP	Poids (kg)
15	½	½	1610.240		350 896 257	614 113	1	0.326
20	¾	¾	1610.320		350 896 258	614 114	1	0.390
25	1	1	1610.400		350 896 259	614 115	1	0.814
32	1 ¼	1 ¼	1610.480		350 896 260	614 116	1	1.090
40	1 ½	1 ½	1610.560		350 896 261	614 117	1	1.200
50	2	2	1610.640		350 896 262	614 118	1	2.040
65	2 ½	2 ½	1610.720		350 898 300	614 121	1	3.310

DN (mm)	GN (inch)	Pouces (inch)	d1 Rp (inch)	d2 G (inch)	d3 Rp (inch)	h (mm)	l (mm)	l2 (mm)	PN (bar)	z1 (mm)	z2 (mm)	⊙ (mm)
15	½	½	½	½	¼	42	65	1	16	10	27	6
20	¾	¾	¾	¾	¼	51	75	3	16	12	33	6
25	1	1	1	1	¼	61	90	3	16	15	40	6
32	1 ¼	1 ¼	1 ¼	1 ¼	¼	80	110	9	16	19	52	6
40	1 ½	1 ½	1 ½	1 ½	¼	91	120	10	16	20	61	6
50	2	2	2	2	¼	107	150	5	16	23	77	6
65	2 ½	2 ½	2 ½	2 ½	¼	116	180		16	22	98	6

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>