



Wafer-style intermediate installation butterfly valve type 565 manual PVDF/PA-GF

With gear box

Wafer style metric/ANSI/BS/JIS

Suitable for ABS, PVC-U, PVC-C, ecoFIT, COOL-FIT and PROGEF Systems

Model:

- Installation length: EN558 row 20, ISO 5752 row 20, API 609 table 2
- Flange standards: ISO 7005 PN10/16, EN 1092 PN10/16, DIN 2501 PN10/16, ANSI/ASME B 16.5 Class 150, BS 1560: 1989 Class 125/150; BS 4504 PN10/16, JIS B 2220 10K, JIS B 2239 10K
- For easy installation and removal
- Suitable for water and water treatment applications (e.g. sea water, drinking water and industrial water)
- Switching Ring for the double sensor for electrical position feedback is pre-assembled. Double sensor can be ordered as accessory

Option:

- Individual configuration of the valve possible
- Hand (lockable hand lever), pneumatic or electric actuators from GF
- Double sensor for electrical position feedback incl. LED feedback

Note:

For some material combination (e.g. DN300 valves with PE/PP pipes) special flange adapters are needed. Please check the "Perfect flange connection tool" on www.gfps.com

d	DN	Size	PN	kv-value	EPDM	SP	Weight	FKM	SP	Weight
(mm)	(mm)	(inch)	(bar)	($\Delta p=1$ bar)	Code		(kg)	Code		(kg)
				(l/min)						
63	50	2	16	1445	199 565 200	1	3.0	199 565 220	1	3.1
75	65	2 1/2	16	2530	199 565 201	1	3.2	199 565 221	1	3.3
90	80	3	16	4020	199 565 202	1	3.4	199 565 222	1	3.5
110	100	4	16	5850	199 565 203	1	4.2	199 565 223	1	4.3
140	125	5	16	11900	199 565 204	1	4.7	199 565 224	1	5.0
160	150	6	16	18050	199 565 205	1	5.5	199 565 225	1	5.8
225	200	8	10	43667	199 565 206	1	6.7	199 565 226	1	7.2
280	250	10	10	62333	199 565 207	1	12.7	199 565 227	1	13.4
315	300	12	6	94500	199 565 208	1	16.5	199 565 228	1	17.6

d	D2	Wmax	Hmax	Lmax	H4	V	V1	Lg	E	LB	LV	M	Y
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
63	100.0	238.5	303.0	169.0	23	133.5	63.0	43	80	128.0	112.5	160	61.5
75	121.0	246.0	329.0	169.0	23	140.0	82.0	46	80	128.0	112.5	160	61.5
90	138.0	248.5	341.5	169.0	23	146.0	89.0	46	80	128.0	112.5	160	61.5
110	158.5	258.5	377.5	169.0	23	166.5	104.0	52	80	128.0	112.5	160	61.5
140	187.0	272.0	405.0	169.0	23	180.0	118.0	56	80	128.0	112.5	160	61.5
160	213.0	285.5	426.5	169.0	23	189.0	130.5	56	80	128.0	112.5	160	61.5
225	267.0	312.5	475.5	169.0	23	209.5	159.0	60	80	128.0	112.5	160	61.5
280	325.5	360.5	603.0	212.5	23	262.5	195.5	68	100	135.5	130.0	200	68.5
315	380.0	387.5	659.5	212.5	23	284.5	230.5	78	100	135.5	130.0	200	68.5

d	Q2
(mm)	(mm)
63	28.5
75	44.0
90	63.5
110	84.0
140	110.5
160	137.5
225	190.5
280	239.0
315	285.5

Data sheet

valid from: 2/8/25



The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>