



SYGEF Plus flare transition fitting PN10

Model:

- Welding dimension: PN16
- Material: PVDF-HP

d	tube size	PN	FM	Code	Weight	L	L1	L2	D	e
(mm)	(inch)	(bar)			(kg)	(mm)	(mm)	(mm)	(mm)	(mm)
20	¾	10	BCF, IR	735 598 430	0.028	75	45	30	21	1.9
20	¾	10	BCF, IR	735 598 431	0.022	76	46	30	23	1.9
20	½	10	BCF, IR	735 598 432	0.034	77	47	30	26	1.9
20	¾	10	BCF, IR	735 598 433	0.043	78	48	30	34	1.9
25	¾	10	BCF, IR	735 598 435	0.033	75	45	30	21	1.9
25	¾	10	BCF, IR	735 598 436	0.025	76	46	30	23	1.9
25	½	10	BCF, IR	735 598 437	0.028	77	47	30	26	1.9
25	¾	10	BCF, IR	735 598 438	0.050	78	48	30	34	1.9
25	1	10	BCF, IR	735 598 439	0.102	87	57	30	46	1.9
32	½	10	BCF, IR	735 598 442	0.036	77	47	30	26	2.4
32	¾	10	BCF, IR	735 598 443	0.048	78	48	30	34	2.4
32	1	10	BCF, IR	735 598 444	0.107	87	57	30	46	2.4

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>