




**SYGEF Plus union (FKM white)**  
**SDR21/PN16**  
**Gap filling O-ring positioning**  
**High Purity clean-room product ISO Class 5 (1)**

**Model:**

- Material: PVDF-HP
- gap filling O-ring positioning
- FDA compliant
- d75, d90 and d110 with buttress shaped thread
- Please see installation instruction



d (mm)	DN (mm)	SDR	PN (bar)	FM	FKM Code	Weight (kg)
20	15	21	16	BCF, IR	<b>735 528 626</b>	0.082
25	20	21	16	BCF, IR	<b>735 528 627</b>	0.123
32	25	21	16	BCF, IR	<b>735 528 628</b>	0.166
40	32	21	16	BCF, IR	<b>735 528 629</b>	0.263
50	40	21	16	BCF, IR	<b>735 528 630</b>	0.372
63	50	21	16	BCF, IR	<b>735 528 631</b>	0.463
75	65	21	16	BCF, IR	<b>735 528 637</b>	0.740
90	80	21	16	BCF, IR	<b>735 528 638</b>	0.798
110	100	21	16	BCF, IR	<b>735 528 639</b>	1.020

d (mm)	O-Ring	O-Ring FKM	Size	L (mm)	L1 (mm)	L2 (mm)	L3 (mm)	L4 (mm)	D (mm)	e (mm)
20	2.62x15.54	749411005	1	106	53	53	25	37	43	1.9
25	3.53x20.22	749411006	1 1/4	112	56	56	25	38	53	1.9
32	3.53x26.58	749411120	1 1/2	118	59	59	25	40	60	2.4
40	3.53x34.52	749411062	2	124	62	62	25	41	74	2.4
50	3.53x44.04	749411172	2 1/4	130	65	65	25	43	82	3.0
63	4.00x55.00	749411054	2 3/4	136	68	68	25	44	100	3.0
75	5.34x69.22	749411013	S 107.5 x 3.6	132	66	66	24	34	133	3.6
90	5.34x81.92	749411014	S 107.5 x 3.6	130	65	65	24	48	133	4.3
110	5.34x101.00	749411015	S 107.5 x 3.6	130	65	65	25	45	155	5.3

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:  
 info.ps@georgfischer.com Internet: <http://www.gfps.com>