




PVC-U 计量球阀 523Pro#
带胶粘承插端 公制

型号:

- 微计量
- 卓越的控制性能
- 安装简单，易拆卸
- PTFE球密封
- 带有刻度，180°操作
- 内置不锈钢固定螺孔
- 尺寸z、阀端和活接螺母与523型球阀兼容



选项:

- 其他材质按需提供



d (mm)	DN (mm)	PN (bar)	kv-value ($\Delta p=1$ bar) (l/min)	EPDM code	SP weight (kg)	FKM code	SP weight (kg)
16	10	10	11	161 523 401	1 0,170	161 523 411	1 0,170
20	15	10	20	161 523 402	1 0,169	161 523 412	1 0,170

d (mm)	M1 (mm)	M2 (mm)	Lz1 (mm)	Lz2 (mm)	L (mm)	V1 (mm)	H (mm)	Hmax (mm)	BG (mm)	B3 (mm)	H4 (mm)	U (mm)	z (mm)
16	35	47	28	28	92	27	72	99	M6	25	12	59	64
20	35	47	28	28	95	27	72	99	M6	25	12	59	64



The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>