




PVDF
Válvula borboleta tipo 567
Com volante redutor

Model:


- Material: PVDF
- Face-a-face conforme EN 558, ISO 5752
- Dimensional: ISO 7005 PN10, EN 1092 PN10, DIN 2501 PN10, ANSI/ASME B16.5 Class 150, BS 1560: 1989, BS 4504, JIS B2220

Note:


For some material combination (e.g. DN300 valves with PE/PP pipes) special flange adapters are needed. Please check the "Perfect flange connection tool" on www.gfps.com



dDimensão (mm)	DN (inch)	PN (mm)	PN (bar)	kv-value ($\Delta p=1$ bar) (l/min)	FKM weight code (kg)	PTFE weight code (kg)
63	2	50	10	740	175 567 022	3,118
75	2 ½	65	10	1500	175 567 023	3,230
90	3	80	10	2400	175 567 024	3,410
110	4	100	10	3800	175 567 025	4,062
140	5	125	10	8600	175 567 026	4,657
160	6	150	10	11400	175 567 027	5,974
225	8	200	10	19900	175 567 028	7,797
280	10	250	10	34000	175 567 029	15,441
315	12	300	10	50000	175 567 030	20,763



d	Hmax	Lmax	Wmax	U	V	H4	V1	Lg	D2	Q1	Q2	k	Y	Y1
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
63	319,4	169,1	240,2	90	133,3	23	78,8	45	104	40		125	61,2	
75	332,3	169,1	247,3	90	139,9	23	85,1	46	115	54	35	145	61,2	
90	344,1	169,1	249,4	90	145,6	23	91,2	49	131	67	50	160	61,2	
110	379,4	169,1	261,5	90	166,4	23	105,7	56	161	88	74	180	61,2	
140	406,1	169,1	274,5	90	180,0	23	118,8	64	187	113	97	210	61,2	
160	427,2	169,1	288,5	90	189,0	23	130,9	72	215	139	123	240	61,2	
225	476,1	169,1	267,0	90	210,5	23	158,3	73	267	178	169	295	61,2	
280	613,0	212,6	329,0	125	262,6	23	206,1	113	329	210	207	350	68,4	17,0
315	657,4	212,6	380,4	125	284,3	23	228,8	113	379	256	253	400	68,4	17,0



d	E	M	LV	LB
(mm)	(mm)	(mm)	(mm)	(mm)
63	80	160	112,3	129,5
75	80	160	112,3	129,5
90	80	160	112,3	129,5
110	80	160	112,3	129,5
140	80	160	112,3	129,5
160	80	160	112,3	129,5
225	80	160	112,3	129,5
280	100	200	130,0	134,0
315	100	200	130,0	134,0

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>