




Metering ball valve type 523 Pro PVC-U With threaded socket NPT

Model:

- Micro-doser
- Excellent control characteristics
- Designed for easy installation and removal
- Ball seals PTFE
- Angle of operation 180° with scale
- Integrated stainless steel mounting inserts
- Z-length, end connectors and union nuts compatible to Type 523



Option:

- Other materials on demand



d	Size	DN	PN	kv-value	EPDM	SP	Weight	FKM	SP	Weight
(mm)	(inch)	(mm)	(bar)	(Δp=1 bar)	Code		(kg)	Code		(kg)
16	3/8	10	10	11	161 523 541	1	0.170	161 523 551	1	0.170
20	1/2	15	10	20	161 523 542	1	0.170	161 523 552	1	0.170

M1	M2	Lz1	Lz2	L	V1	H	Hmax	DE	BG	B3	H4	U	z
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)		(mm)	(mm)	(mm)	(mm)
35	47	28	28	92	27	72	99	50	M6	25	12	59	73
35	47	28	28	95	27	72	99	50	M6	25	12	59	71



The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>