



## Check valve type 562 PVC-C With Sanipex MT valve end

### Model:

- For horizontal or vertical installation
- Sealing at a minimum water column of 1m
- Spring loaded, spring made of stainless steel (1.4310)
- Spring available in other materials, see spare parts
- Designed for easy installation and removal
- Vibration free even at high flow velocity
- Flow-optimised return cone, double guided
- Compact installation length, same as ball valve type 546
- Z-length, end connectors and union nuts **not** compatible with type 360

| d    | DN   | PN    | kv-value            | EPDM               | Weight | FKM                | Weight |
|------|------|-------|---------------------|--------------------|--------|--------------------|--------|
| (mm) | (mm) | (bar) | ( $\Delta p=1$ bar) | Code               | (kg)   | Code               | (kg)   |
|      |      |       | (l/min)             |                    |        |                    |        |
| 16   | 10   | 16    | 190                 | <b>700 247 301</b> | 0.120  | <b>700 247 311</b> | 0.120  |
| 20   | 15   | 16    | 180                 | <b>700 247 302</b> | 0.120  | <b>700 247 312</b> | 0.120  |
| 25   | 20   | 16    | 380                 | <b>700 247 303</b> | 0.260  | <b>700 247 313</b> | 0.280  |
| 32   | 25   | 16    | 460                 | <b>700 247 304</b> | 0.280  | <b>700 247 314</b> | 0.280  |
| 40   | 32   | 16    | 850                 | <b>700 247 305</b> | 0.490  | <b>700 247 315</b> | 0.490  |
| 50   | 40   | 16    | 1080                | <b>700 247 306</b> | 0.710  | <b>700 247 316</b> | 0.710  |
| 63   | 50   | 16    | 1670                | <b>700 247 307</b> | 1.460  | <b>700 247 317</b> | 1.470  |

| d    | D    | L    | L2   | z    | closest         |
|------|------|------|------|------|-----------------|
| (mm) | (mm) | (mm) | (mm) | (mm) | inch            |
|      |      |      |      |      | (inch)          |
| 16   | 50   | 146  | 56   | 108  | $\frac{3}{8}$   |
| 20   | 50   | 160  | 56   | 112  | $\frac{1}{2}$   |
| 25   | 58   | 191  | 65   | 133  | $\frac{3}{4}$   |
| 32   | 68   | 215  | 71   | 141  | 1               |
| 40   | 84   | 257  | 85   | 169  | 1 $\frac{1}{4}$ |
| 50   | 97   | 297  | 89   | 197  | 1 $\frac{1}{2}$ |
| 63   | 124  | 362  | 101  | 237  | 2               |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:  
info.ps@georgfischer.com Internet: <http://www.gfps.com>