



Return flow inhibitor, PN 16

- Temperature: max. 90°C
- Material: gunmetal, stainless steel, EPDM, plastic
- Opening pressure: < 5 kPa (< 50 mbar)
- Connection: female thread

DN (mm)	GN (inch)	Size (inch)	JRG Code	GF Code	SP	Weight (kg)
15	½	½	1610.240	350 896 257	1	0.326
20	¾	¾	1610.320	350 896 258	1	0.390
25	1	1	1610.400	350 896 259	1	0.814
32	1 ¼	1 ¼	1610.480	350 896 260	1	1.090
40	1 ½	1 ½	1610.560	350 896 261	1	1.200
50	2	2	1610.640	350 896 262	1	2.040
65	2 ½	2 ½	1610.720	350 898 300	1	3.310

DN (mm)	GN (inch)	Size (inch)	d1 Rp (inch)	d2 G (inch)	d3 Rp (inch)	h (mm)	l (mm)	l2 (mm)	PN (bar)	z1 (mm)	z2 (mm)	⌀ (mm)
15	½	½	½	½	¼	42	65	1	16	10	27	6
20	¾	¾	¾	¾	¼	51	75	3	16	12	33	6
25	1	1	1	1	¼	61	90	3	16	15	40	6
32	1 ¼	1 ¼	1 ¼	1 ¼	¼	80	110	9	16	19	52	6
40	1 ½	1 ½	1 ½	1 ½	¼	91	120	10	16	20	61	6
50	2	2	2	2	¼	107	150	5	16	23	77	6
65	2 ½	2 ½	2 ½	2 ½	¼	116	180		16	22	98	6

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>