



Wafer-Style, intermediate installation butterfly valve metal type 039
With gear box
Flange standard Metric/Inch/ASTM - PN10
Disc: stainless steel DIN Norm 1.4408 without coating

Model:

- Wafer Style
- Body GGG40 (A 395 / A395 M-99, EN-JIS 1020 EN1563) Rilsan® coating
- Installation length: EN 558 row 20
- Pressure range: 16 bar (DN 50-300)
- Interface according to DIN EN ISO 5211
- Axis DN50 - DN300: Single-piece axis with square profile, material stainless steel DIN Norm 1.4021
- Flange connection: DN50 - DN300: PN6, PN10, ANSI 125/150 Lbs., BS 10-D/E

Option:

- Electric and pneumatic actuator on request
- Other liner material on request

d (mm)	DN (mm)	Size (inch)	PN (bar)	kv-value ($\Delta p=1$ bar) (L/min)	Liner: EPDM Code	SP	Weight (kg)
63	50	2	16	3167	199 039 226	1	6.40
75	65	2 ½	16	4667	199 039 227	1	0.00
90	80	3	16	7167	199 039 228	1	3.80
110	100	4	16	11833	199 039 229	1	4.80
140	125	5	16	18333	199 039 230	1	5.60
160	150	6	16	26667	199 039 231	1	7.00
225	200	8	16	46667	199 039 232	1	9.50
280	250	10	16	78333	199 039 233	1	19.00
315	300	12	16	115000	199 039 234	1	37.00

d (mm)	Liner: FKM Code	Liner: EPDM DVGW Code	Liner: NBR Code	PF
63	199 039 239	199 039 470	199 039 380	3 39 226 263
75	199 039 240	199 039 471	199 039 381	3 39 226 263
90	199 039 241	199 039 472	199 039 382	3 39 226 263
110	199 039 242	199 039 473	199 039 383	3 39 226 263
140	199 039 243	199 039 474	199 039 384	3 39 226 263
160	199 039 244	199 039 475	199 039 385	3 39 226 263
225	199 039 245	199 039 476	199 039 386	3 39 226 263
280	199 039 246	199 039 477	199 039 387	3 39 226 263
315	199 039 247	199 039 478	199 039 388	3 39 226 263

d (mm)	D3 (mm)	D4 (mm)	D5 (mm)	H (mm)	H1 (mm)	H2 (mm)	H3 (mm)	L1 (mm)	L2 (mm)	L3 (mm)	L4 (mm)	Q (mm)
63	102	165	125	278	83	140	55	84	152	38	107	32
75	122	185	125	300	93	152	55	84	152	38	107	51
90	139	190	125	312	98	159	55	84	152	38	107	69
110	159	229	125	344	111	178	55	84	152	38	107	89
140	189	254	125	373	127	191	55	84	152	38	107	115
160	214	285	125	409	143	203	63	84	152	38	107	143
225	269	343	125	480	172	245	63	84	152	38	107	194
280	331	333	250	542	204	275	63	106	184	52	142	243
315	380	353	250	620	242	315	63	106	184	52	142	293

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Data sheet

valid from: 12/13/24



Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>