



O-ring FKM white
For unions with gap filling O-ring positioning
High Purity clean-room product ISO Class 5 (100)

Model:

- For unions with gap filling O-ring position
- Hardness approx. 65° Shore
- FKM white min. temperature -15°C

| d (mm) | FKM Code | Weight (kg) | D (mm) | D1 (mm) | D2 (mm) |
|-----------|--------------------|----------------|-----------|------------|------------|
| 20 | 749 411 005 | 0.002 | 20.6 | 15.5 | 2.62 |
| 25 | 749 411 006 | 0.002 | 27.3 | 20.2 | 3.53 |
| 32 | 749 411 120 | 0.002 | 33.6 | 26.6 | 3.53 |
| 40 | 749 411 062 | 0.002 | 41.6 | 34.5 | 3.53 |
| 50 | 749 411 172 | 0.003 | 51.1 | 44.0 | 3.53 |
| 63 | 749 411 054 | 0.003 | 63.0 | 55.0 | 4.00 |
| 75 | 749 411 013 | 0.010 | 79.9 | 69.2 | 5.33 |
| 90 | 749 411 014 | 0.012 | 92.6 | 81.9 | 5.33 |
| 110 | 749 411 015 | 0.015 | 117.0 | 101.0 | 5.33 |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>