



Type 2536 Rotor-X Standard Mount Paddlewheel

Flow:

- Operating range: 0.1 to 6 m/s, 0.3 to 20 ft/s
- Open collector output
- Installs into pipe sizes: DN15 to DN900, 0.5 to 36 in
- Max Pressure rating: PP 12.5 bar @ 20 °C, 180 psi @ 68 °F PVDF 14 bar @ 20 °C, 200 psi @ 68 °F
- Rotor: PVDF
- Compatibility: 8900, 9900, 9900-1BC, 9950
- Power source: <20mA @ 3.3 to 24 VDC
- *Only Signet installation fittings
- PVC 2536 version DN15 to DN100 (½ to 4 in.) for concentrated Sodium Hypochlorite 12.5% dosing application in water treatment
- Standard: FKM O-rings (EPDM or FFKM on request)
- Other materials of rotor and axis on request

MFR #	Body	Rotor Pin	Pin	Insertion Sensor Length	Pipe Size (inch)	Sensor Type
3-2536-P0	PP	Black PVDF	Titanium	X0 (DN15 – DN100, 1/2" to 4")	0.5 - 4.0	Remote Mount
3-2536-P1	PP	Black PVDF	Titanium	X1 (DN125 – DN200, 5" to 8")	5.0 - 8.0	Remote Mount
3-2536-P2	PP	Black PVDF	Titanium	X2 (DN250 – DN900, 10" to 36")	10.0 - 36.0	Remote Mount
3-2536-T0	PVDF	PVDF	PVDF	X0 (DN15 – DN100, 1/2" to 4")	0.5 - 4.0	Remote Mount
3-2536-V0	PVDF	PVDF	Hastelloy C	X0 (DN15 – DN100, 1/2" to 4")	0.5 - 4.0	Remote Mount
3-2536-V1	PVDF	PVDF	Hastelloy C	X1 (DN125 – DN200, 5" to 8")	5.0 - 8.0	Remote Mount
3-2536-U0	PVC-U	ECTFE	Titanium	X0 (DN15 – DN100, 1/2" to 4")	0.5 - 4.0	Remote Mount

Code

198 840 143

198 840 144

198 840 145

198 840 149

198 840 146

198 840 147

159 001 843

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>