






PROGEF 标准型
气动球阀546Pro PP-H#DA (双作用)
带承插焊-承插端 公制

型号:

- Namur标准气源接口满足VDI/DE 3845
- 整体耐腐蚀塑料方案(气动执行器外壳材质 PP-GF)
- 带可视机械式位置指示
- 内置不锈钢固定螺孔
- Z尺寸、阀端和活接螺母与546型球阀 (第1代) 兼容

选项:

- 可配Double Sensor阀位反馈器, 带LED指示, 信号类型PNP, NPN和Namur
- 可选配定位器RPC, RPC D, RPC PID
- 可提供其他阀门配置



d	DN	Size	PN	kv-value	EPDM	SP	weight	FKM	SP	weight
(mm)	(mm)	(inch)	(bar)	($\Delta p=1$ bar)	code		(kg)	code		(kg)
				(l/min)						
16	10	$\frac{3}{8}$	10	70	199 251 202	1	1,200	199 251 212	1	1,200
20	15	$\frac{1}{2}$	10	185	199 251 203	1	0,766	199 251 213	1	0,774
25	20	$\frac{3}{4}$	10	350	199 251 204	1	0,844	199 251 214	1	1,300
32	25	1	10	700	199 251 205	1	0,920	199 251 215	1	0,919
40	32	$1\frac{1}{4}$	10	1000	199 251 206	1	2,500	199 251 216	1	2,500
50	40	$1\frac{1}{2}$	10	1600	199 251 207	1	1,691	199 251 217	1	1,701
63	50	2	10	3100	199 251 208	1	3,700	199 251 218	1	3,700
75	65	$2\frac{1}{2}$	10	5000	199 251 209	1	5,400	199 251 219	1	5,400
90	80	3	10	7000	199 251 210	1	7,700	199 251 220	1	7,700
110	100	4	10	11000	199 251 211	1	10,800	199 251 221	1	10,800

d	Actuator	B3	B5	da2	DE1	E	G	G1	H	H2	H4	L	Lz	M
(mm)		(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
16	PPA08	25	16,2	33	50	74	M6	M5	155	20	12	93	28	128
20	PPA08	25	16,2	33	50	74	M6	M5	155	20	12	95	28	128
25	PPA08	25	17,5	33	58	74	M6	M5	159	20	12	109	33	128
32	PPA08	25	17,5	33	68	94	M6	M5	178	20	12	119	36	128
40	PPA15	45	23,3	33	84	94	M8	M5	184	20	15	135	43	159
50	PPA15	45	23,3	33	97	120	M8	M5	213	20	15	147	45	159
63	PPA40	45	24,3	33	124	120	M8	M5	228	20	15	168	51	184
75	PPA40	70	28,5	33	166	142	M8	M5	277	20	15	233	38	184
90	PPA40	70	28,5	33	200	142	M8	M5	289	20	15	254	71	184
110	PPA80	120	28,5	33	238	142	M12	M5	324	20	22	301	82	261

d	V1	X5	X6	X7	X10	z
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
16	27	80	30	43	38,0	67
20	27	80	30	43	38,0	66
25	30	80	30	43	41,9	77
32	36	80	30	51	47,0	83
40	44	80	30	51	53,5	99
50	51	80	30	62	62,8	105
63	64	80	30	62	77,0	117
75	85	80	30	74	119,0	167
90	105	80	30	74	131,0	180
110	123	80	30	74	145,0	215

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Data sheet

valid from: 2025/2/8



Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>