



**Type 2850 Conductivity/Resistivity
Sensor Electronics**

Conductivity/Resistivity:

- Accepts any cell constant
- Compatible with all Signet Conductivity Sensors
- Output choices include digital (S3L) for use with the Signet 8900 of 4 to 20mA
- Compatible with Signet Instrument Type 8900 or instruments accepting a 4 to 20mA output
- Single or dual input available for remote mount version (S3L) only

Body	Process Con- nection	Process Con- nection Size	MFR #	Mounting	Output
			3-2850-51	3/4 inch FNPT	Digital (S3L), one input
PBT	Thread	3/4 inch	3-2850-52	3/4 inch FNPT	4 - 20mA, one input
PBT			3-2850-61	Universal Mount	Digital (S3L), one input
PBT			3-2850-62	Universal Mount	4 - 20mA, one input
PBT			3-2850-63	Universal Mount	Digital (S3L), one or two inputs

Code

159 001 398
159 001 399
159 001 400
159 001 401
159 001 402

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>