



PVC-U Kugelhahn Typ 546 Pro Mit Klebestutzen PVC-U ISO

Ausführung:

- Serienmässig abschliessbar
- Kugeldichtung aus PTFE
- Integrierte Gewindebuchsen Edelstahl für die Befestigung der Armatur
- z-Mass, Anschlusssteil und Überwurfmutter **sind kompatibel** zu Typ 546 (1. Generation)

Option:

- Schnittstellenmodul mit Positionsrückmeldung inkl. LED Sensor (PNP, NPN und NAMUR)
- Manuelle Federrückstelleinheit ("Dead man") (DN10-25)
- Stellantriebe pneumatisch und elektrisch von Georg Fischer
- Armatur individuell konfigurierbar



d	DN	Zoll	PN	kv-Wert	EPDM	NPK	SP	Gewicht
(mm)	(mm)	(inch)	(bar)	($\Delta p=1$ bar)	Code			(kg)
				(l/min)				
16	10	3/8	16	71	161 546 721	581 151	1	0.157
20	15	1/2	16	185	161 546 722	581 152	1	0.157
25	20	3/4	16	350	161 546 723	581 153	1	0.242
32	25	1	16	700	161 546 724	581 154	1	0.359
40	32	1 1/4	16	1000	161 546 725	581 155	1	0.620
50	40	1 1/2	16	1600	161 546 726	581 156	1	0.869
63	50	2	16	3100	161 546 727	581 157	1	1.550
75	65	2 1/2	16	5000	161 546 728	581 158	1	3.689
90	80	3	16	7000	161 546 729	581 161	1	5.512
110	100	4	16	11000	161 546 730	581 162	1	11.900

d	FKM	NPK	SP	Gewicht
(mm)	Code			(kg)
16	161 546 731		1	0.157
20	161 546 732		1	0.157
25	161 546 733		1	0.242
32	161 546 734		1	0.347
40	161 546 735		1	0.620
50	161 546 736		1	0.845
63	161 546 737		1	1.550
75	161 546 738		1	5.100
90	161 546 739		1	7.500
110	161 546 740		1	11.900

d	B3	DE1	G	H	H1	H4	L	Lz	M	M1	M2	s1	z
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
16	25	50	M6	60.5	27	12	114	28	82	35	47	3.0	88
20	25	50	M6	60.5	27	12	124	28	82	35	47	3.0	96
25	25	58	M6	74.0	30	12	144	33	106	44	62	3.0	112
32	25	68	M6	80.0	36	12	154	36	106	44	62	4.0	118
40	45	84	M8	95.0	44	15	174	43	131	57	74	4.5	134
50	45	97	M8	101.5	51	15	194	45	131	57	74	5.5	148
63	45	124	M8	116.5	64	15	224	51	152	66	86	7.0	170
75	70	166	M8	169.0	85	15	284	68	270	64	205	8.5	194
90	70	200	M8	180.0	105	15	300	71	270	64	205	10.0	196
110	120	238	M12	194.0	123	22	340	82	326	71	205	12.0	212

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>