



## Male adaptor

- installation without disassembling
- suitable for PE and PEX pipes
- water PN16
- material: PP
- gasket: EPDM quality for drinkable water
- male thread: ISO 7 (conical)
- colour: blue-black

| d    | R      | PN    | Code        | SP | GP  | Weight | D    | L    | I1   | I2   | I3   |
|------|--------|-------|-------------|----|-----|--------|------|------|------|------|------|
| (mm) | (inch) | (bar) |             |    |     | (kg)   | (mm) | (mm) | (mm) | (mm) | (mm) |
| 16   | ½      | 16    | 158 400 351 | 10 | 70  | 0.043  | 45   | 73   | 46   | 19   | 14   |
| 16   | ¾      | 16    | 158 400 352 | 10 |     | 0.043  | 51   | 74   | 46   | 19   | 14   |
| 20   | ½      | 16    | 158 400 123 | 10 | 220 | 0.039  | 45   | 73   | 54   | 19   | 14   |
| 20   | ¾      | 16    | 158 400 124 | 10 |     | 0.040  | 45   | 74   | 54   | 19   | 15   |
| 20   | 1      | 16    | 158 400 125 | 10 |     | 0.042  | 45   | 77   | 54   | 19   | 17   |
| 25   | ½      | 16    | 158 400 126 | 10 |     | 0.057  | 53   | 79   | 59   | 21   | 14   |
| 25   | ¾      | 16    | 158 400 127 | 10 |     | 0.057  | 53   | 80   | 59   | 21   | 15   |
| 25   | 1      | 16    | 158 400 128 | 10 |     | 0.060  | 53   | 83   | 59   | 21   | 17   |
| 32   | ¾      | 16    | 158 400 129 | 10 |     | 0.090  | 64   | 88   | 66   | 23   | 15   |
| 32   | 1      | 16    | 158 400 130 | 10 |     | 0.091  | 64   | 91   | 66   | 23   | 17   |
| 32   | 1 ¼    | 16    | 158 400 131 | 10 |     | 0.095  | 64   | 93   | 66   | 23   | 20   |
| 32   | 1 ½    | 16    | 158 400 132 | 10 | 110 | 0.098  | 64   | 93   | 66   | 23   | 20   |
| 40   | 1      | 16    | 158 400 133 | 90 |     | 0.141  | 75   | 102  | 76   | 26   | 17   |
| 40   | 1 ¼    | 16    | 158 400 134 | 90 |     | 0.145  | 75   | 104  | 76   | 26   | 20   |
| 40   | 1 ½    | 16    | 158 400 135 | 90 |     | 0.144  | 75   | 104  | 76   | 26   | 20   |
| 40   | 2      | 16    | 158 400 136 | 1  | 80  | 0.155  | 75   | 109  | 76   | 26   | 24   |
| 50   | 1      | 16    | 158 400 137 | 1  | 50  | 0.269  | 97   | 114  | 88   | 30   | 17   |
| 50   | 1 ¼    | 16    | 158 400 138 | 50 |     | 0.252  | 97   | 117  | 88   | 30   | 20   |
| 50   | 1 ½    | 16    | 158 400 139 | 50 |     | 0.276  | 97   | 117  | 88   | 30   | 20   |
| 50   | 2      | 16    | 158 400 140 | 50 |     | 0.283  | 97   | 121  | 88   | 30   | 24   |
| 63   | 1 ½    | 16    | 158 400 141 | 30 |     | 0.471  | 114  | 135  | 104  | 35   | 20   |
| 63   | 2      | 16    | 158 400 142 | 30 |     | 0.470  | 114  | 139  | 104  | 35   | 24   |
| 63   | 2 ½    | 16    | 158 400 143 | 25 |     | 0.476  | 114  | 143  | 104  | 35   | 28   |
| 75   | 2      | 16    | 158 400 144 | 1  | 18  | 0.773  | 135  | 170  | 133  | 41   | 24   |
| 75   | 2 ½    | 16    | 158 400 145 | 10 |     | 0.782  | 135  | 174  | 133  | 41   | 28   |
| 75   | 3      | 16    | 158 400 146 | 18 |     | 0.788  | 135  | 177  | 133  | 41   | 30   |
| 90   | 2      | 16    | 158 400 147 | 1  | 8   | 1.247  | 161  | 189  | 150  | 44   | 24   |
| 90   | 2 ½    | 16    | 158 400 148 | 1  | 8   | 1.248  | 161  | 193  | 150  | 44   | 28   |
| 90   | 3      | 16    | 158 400 149 | 8  |     | 1.251  | 161  | 196  | 150  | 44   | 30   |
| 90   | 4      | 16    | 158 400 150 | 1  | 8   | 1.319  | 161  | 202  | 150  | 44   | 36   |
| 110  | 3      | 16    | 158 400 151 | 1  | 6   | 1.821  | 185  | 222  | 175  | 53   | 30   |
| 110  | 4      | 16    | 158 400 152 | 1  | 6   | 1.858  | 185  | 228  | 175  | 53   | 36   |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>