


过渡直接 PE/铜(Ms 58) 外螺纹



- PE100 S5/SDR11
- 压力等级：气10bar/水16bar
- 带一体管道固定装置
- 4mm连接端
- 焊接指示
- Supplied as a kit with ELGEF Plus coupler or *ELGEF Plus reducer



d	Thread Type	Size	DN	PN	code	weight
(mm)		(inch)	(mm)	(bar)		(kg)
20	R	1/2	15	16	720 920 756	0,187
20	R	1	15	16	720 920 754	0,344
25	R	3/4	20	16	720 920 757	0,254
25	R	1	20	16	720 920 763	0,340
32	R	1/2	25	16	720 920 764	0,213
32	R	3/4	25	16	720 920 765	0,268
32	R	1	25	16	720 920 758	0,340
32	R	1 1/4	25	16	720 920 766	0,489
32	R	1 1/2	25	16	720 920 767	0,635
32	R	2	25	16	720 920 768	1,000
40	R	1	32	16	720 920 771	0,364
40	R	1 1/4	32	16	720 920 759	0,514
40	R	1 1/2	32	16	720 920 772	0,645
40	R	2	32	16	720 920 773	0,961
50	R	1	40	16	720 920 776	0,367
50	R	1 1/4	40	16	720 920 777	0,554
50	R	1 1/2	40	16	720 920 760	0,652
50	R	2	40	16	720 920 778	0,971
63	R	1	50	16	720 920 781	0,441
63	R	1 1/4	50	16	720 920 782	0,600
63	R	1 1/2	50	16	720 920 783	0,712
63	R	2	50	16	720 920 761	0,943

d	Do	Lmax	P1	SLW	SDR pipe
(mm)	(mm)	(mm)	(mm)	(mm)	
20	31	110	34	30	9-11
20	44	124	34	40	9-11
25	36	111	34	35	9-11
25	44	124	34	40	9-11
32	44	121	34	30	9-11
32	44	122	34	35	9-11
32	44	117	34	40	9-11
32	54	135	34	50	9-11
32	60	143	34	60	9-11
32	81	157	34	70	9-11
40	54	133	39	40	9-11
40	54	127	39	50	9-11
40	66	143	39	60	9-11
40	81	157	39	70	9-11
50	66	141	43	40	9-11
50	66	143	43	50	9-11
50	66	135	43	60	9-11
50	81	157	43	70	9-11
63	81	151	46	40	9-11
63	81	153	46	40	9-11
63	81	153	46	60	9-17.6
63	81	147	46	70	9-17.6

Data sheet

valid from: 2025/1/25



The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>