



MD 160 Compact butt fusion machine

- Portable butt fusion machine for use in the workshop and on job site
- For jointing PE, PP pipes and fittings in the dimensional range d 50 – 160 mm, up to wall thickness of SDR 11
- Light and sturdy base machine (13.8 kg weight with clamping units) suitable for direct use on the installed pipeline
- Suitable for prefabrication of segmented elbows and bends, with maximum jointing angle of 30° (table support included)
- Each clamping unit consists of a narrow clamp, suitable also for short-end fittings, and the pipe support
- The complete reductions inserts set d 50 – 140 mm for clamps and pipe supports is included
- Additional clamps, to be placed at the left and right outer sides, are available as accessories
- Handwheel for easy moving of machine carriage
- Exact pressure adjustment via direct spring load transfer
- Powerful parallel planer for single or double-sided facing of pipe ends
- High performance, electronically controlled heating element
- Including transport packaging and machine specific tool set

d-d (mm)	Performance	Code	Weight (kg)
50 - 160	230 V/1800 W	790 109 006	57.000
50 - 160	115 V/1800 W	790 109 007	57.000

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>